



ABN 43 064 478 842

231 Osborne Avenue Clayton South, VIC 3169  
PO Box 1548, Clayton South, VIC 3169  
t 03 9265 7400 f 03 9558 0875  
freecall 1800 680 680  
www.tmgtestequipment.com.au

## Test & Measurement

- > sales
- > rentals
- > calibration
- > repair
- > disposal

## Complimentary Reference Material

This PDF has been made available as a complimentary service for you to assist in evaluating this model for your testing requirements.

TMG offers a wide range of test equipment solutions, from renting short to long term, buying refurbished and purchasing new. Financing options, such as Financial Rental, and Leasing are also available on application.

TMG will assist if you are unsure whether this model will suit your requirements.

Call TMG if you need to organise repair and/or calibrate your unit.

If you click on the "Click-to-Call" logo below, you can call us for FREE!

TMG Corporate Website

TMG Products Website



Click-to-Call  
TMG Now



Product Lifecycle Management System

### Disclaimer:

All trademarks appearing within this PDF are trademarks of their respective owners.



# EXFO



## FLS-235B

## Pocket Pal Visual Fault Locator

### Easy to use

The Pocket Pal is the easiest way to identify fibers from end to end and polished connector end faces. Its red laser shines through most yellow-jacketed fibers to help you pinpoint breaks, bends, faulty connectors, splices, and other causes of signal loss. It has a reach of up to 5 km\*. The convenient FLS-235B locates faults visually by creating a bright red glow at the exact location of the fault on singlemode or multimode fibers.

### Easy to carry

Due to its small size, light weight, and simple but proven design, the Pocket Pal can accompany you anywhere. In your pocket or belt pouch, carry your FLS-235B to the most demanding environments. To ensure ruggedness, it features rubber seals, a fully enclosed laser head, and a long-lasting On/Off switch. It has been tested to provide reliable operation under intensive use and harsh conditions.

**Bright red laser at  
635 or 670 nm**

**Pulsed and continuous  
operation**

**80 hours of operation in  
flashing mode (typical)**

**Standard AA  
alkaline batteries**

**Rugged and weatherproof**

**FC, ST, or SC connector**

**Compliant with Bellcore  
TR-NWT-001319 optical  
power requirements**

### Easy on batteries

The Pocket Pal's extremely high efficiency guarantees prolonged operation with two standard AA alkaline batteries. The Pulsed mode typically provides 80 hours of uninterrupted flashing operation, while the Continuous mode operates during 40 hours. For added safety and convenience, an LED indicator confirms whether the laser is on or off.

### Easy on your budget

Priced to accommodate the tightest budgets, the FLS-235B Pocket Pal is a truly affordable way to locate faults in OTDR dead zones. Its effectiveness justifies purchasing one for just about every fiber technician.

*\* Typical length of continuous fiber at which end-to-end identification is possible. Visual fault location depends on ambient light conditions at test site.*

## SPECIFICATIONS

Model	FLS-235B1	FLS-235B3
Operation	CW/1 Hz	CW/1 Hz
Wavelength (nm)	635 ±10	670 ±10
Emitter type	laser	laser
Power output (typical) (mW)	0.80	0.80
Distance range	5 km 3 mi.	5 km 3 mi.

## GENERAL SPECIFICATIONS

Power supply	2 AA alkaline batteries		
Laser class	2		
Battery life <sup>1</sup> (hr)	continuous	40	
	flashing	80	
Length	19.6 cm	7 3/4 in.	
Maximum diameter	3.2 cm	1 1/4 in.	
Weight	empty	135 g	4.8 oz.
	with batteries	180 g	6.3 oz.
Temperature	operating	-10° to 50°C	14° to 122°F
	storage	-40° to 85°C	-40° to 185°F

## STANDARD ACCESSORIES

Instruction manual, two AA alkaline batteries, soft pouch and wrist strap, and Certificate of Compliance

## ORDERING INFORMATION

FLS-235BX-XX	
Source code	Connector code
1 = 635 nm	50 = FC/PC
3 = 670 nm	54 = SC/PC
	74 = ST/PC

## NOTES


1. Typical battery life using AA alkaline batteries. Battery life may fluctuate significantly, depending on a specific unit's laser current.

## PRODUCT SELECTION GUIDE


Choosing the right wavelength for your applications is important. The three wavelength options, 635, 650, and 670 nm, have different properties. Each wavelength has its own merits and should be selected in light of its intended purpose.

Model number	Wavelength/Features	Applications	Selection criteria	Comments
FLS-235B1	635 nm • Excellent visibility • Highest attenuation	• Short distances • Fault location at, or near the launch point • OTDR front-end dead zone	• Appears approximately six times brighter than 670 nm at launch point • Light intensity will decrease more rapidly along the fiber	• Has the brightest appearance • Best short-range visibility/price ratio • Not as good as 650 or 670 nm in long fiber span (loses its visibility edge over 6000 ft. or 1.8 km)
FLS-235B3	670 nm • Good visibility • Lowest attenuation	• End-to-end identification • Long spans • Fault location beyond 6000 ft. or 1.8 km	• Reaches farther out than 650 and 635 nm • Appears less bright at launch point	• Most affordable of all • Within capital tools budget of most companies • Unbeatable distance range per dollar ratio
FLS-230A (Ask for a separate data sheet)	650 nm • Very good visibility • Moderate attenuation	• All applications • Both short and long ranges	• Optimized for high visibility and distance range	• Best overall performance • Provides the most flexibility

## SIX WAYS TO USE A VISUAL FAULT LOCATOR



Detects breaks in OTDR dead zone      Highlights sharp bends where losses occur      Mechanical/fusion splice optimization



Detects defective connectors      End-to-end fiber identification in multifiber cables      Detects major scratches on connector surface



EXFO is certified ISO 9001 and attests to the quality of its products. These products are accompanied by a 12-month warranty and an excellent after-sales support service.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

EXFO has made every effort to ensure that the information contained in this brochure is accurate. However, we accept no responsibility for any errors or omissions, and we reserve the right to modify design, characteristics, and products at any time without obligation.

Contact EXFO for prices and availability or to obtain the phone number of your local EXFO distributor.



1 800 663-3936  
info@exfo.com  
www.exfo.com



**CORPORATE HEADQUARTERS:** 465 Godin Avenue, Vanier QC G1M 3G7, Canada Tel.: (418) 683-0211 Fax: (418) 683-2170

**EXFO AMERICA:** 903 North Bowser, Suite 360, Richardson, TX, 75081, USA Tel.: 1 800 663-3936 Fax: (972) 907-2297

**EXFO EUROPE:** Centre d'Affaires-Les Metz, 100, rue Albert Calmette, 78353 Jouy-en-Josas, France Tel.: +33 1 34 63 00 20 Fax: +33 1 34 65 90 93