



ABN 43 064 478 842

➤ 231 osborne avenue clayton south, vic 3169
PO box 1548, clayton south, vic 3169
t 03 9265 7400 f 03 9558 0875
freecall 1800 680 680
www.tmgtestequipment.com.au

Test & Measurement

- sales
- rentals
- calibration
- repair
- disposal

Complimentary Reference Material

This PDF has been made available as a complimentary service for you to assist in evaluating this model for your testing requirements.

TMG offers a wide range of test equipment solutions, from renting short to long term, buying refurbished and purchasing new. Financing options, such as Financial Rental, and Leasing are also available on application.

TMG will assist if you are unsure whether this model will suit your requirements.

Call TMG if you need to organise repair and/or calibrate your unit.

If you click on the “Click-to-Call” logo below, you can call us for FREE!

TMG Corporate Website

TMG Products Website



Click-to-Call
TMG Now



Disclaimer:

All trademarks appearing within this PDF are trademarks of their respective owners.



Specifications

GWRD 0801 (SMR)Receiver

| | |
|--|---|
| Frequency Coverage | 806 - 824; and 851 - 869 MHz dual bands switched inside the receiver |
| Tuning resolution | 10 kHz; 12.5 kHz; 15 kHz |
| Tuning time (\leq 18 Mhz in selected band) | 10 ms |
| Sensitivity (12 dB Sinad) | < -116 dBm |

RSSI Accuracy

| Temperature Range | Accuracy Over RSSI level and Frequency |
|------------------------|--|
| 68 to 80 $^{\circ}$ F | \pm 1 dB -120 to -55 dBm |
| | \pm 2 dB -55 to -45 dBm |
| 32 to 122 $^{\circ}$ F | \pm 2 dB -120 to -55 dBm |
| | \pm 4 dB -55 to -45 dBm |

| | |
|--|-------------------------|
| IF Bandwidth | 18 kHz typical (3 dB) |
| Selectivity (RS-204 Adjacent Channel) | -70 dB |
| Spurious | -65 dBc |
| Audio Distortion | 5% |
| Input VSWR | < 2:1 |
| Maximum input level | +10 dBm |

