

ABN 43 064 478 842

231 osborne avenue clayton south, vic 3169
 PO box 1548, clayton south, vic 3169
 t 03 9265 7400 f 03 9558 0875
 freecall 1800 680 680
 www.tmgtestequipment.com.au

## Test & Measurement

## **Complimentary Reference Material**

sales
 rentals
 calibration
 repair
 disposal
 This PDF has been made available as a complimentary service for you to assist in evaluating this model for your testing requirements.
 TMG offers a wide range of test equipment solutions, from renting short to long term, buying refurbished and purchasing new. Financing options, such as Financial Rental, and Leasing are also available on application.
 TMG will assist if you are unsure whether this model will suit your requirements.
 Call TMG if you need to organise repair and/or calibrate your unit.
 If you click on the "Click-to-Call" logo below, you can all us for FREE!



### **Disclaimer:**

All trademarks appearing within this PDF are trademarks of their respective owners.







## Spirent TestCenter™ 10-GIGABIT ETHERNET MULTIPLE MSA TEST SOLUTION

The increased development of 10 Gigabit Ethernet (10GbE) has resulted in it becoming the preferred technology for increasing bandwidth in data centers to interconnect large enterprise networks. This expansion has also brought about deployment of 10GbE interfaces on the customer edge and in all types of service provider networks. Spirent TestCenter helps meet the expanding market needs of 10GbE by providing implementation of the latest protocols and supporting the newest interfaces.

The Spirent TestCenter 10GbE test modules provide functional, performance, system and conformance testing capabilities from Layer 2 through Layer 7 on a single GUI and test automation platform.

These test modules generate realistic traffic from Layer 2 through Layer 7 of the OSI network layers and analyze data frame, packet, stream and protocol metrics for each layer. The test modules can also simultaneously manage data plane tests with control plane traffic required for metropolitan, enterprise and broadband access routing. They provide the most realistic and accurate network device performance measurements in the industry. Features such as real-time capture and decode along with the real-time event logging system allow the user to find the source of more complex multi-protocol problems.

## **APPLICATIONS**

- Spirent TestCenter supports two different levels of MSA modules. The MSA-1001B test module provides affordable and complete Layer 2 and Layer 3 functional and LAN switching along with functional, system, conformance and performance benchmark testing for both 10GbE LAN and WAN protocols. The high performance MSA-2001B test module provides highly scalable Layer 2-7 capability for the 10GbE LAN and WAN protocols. The MSA-2001B also offers high capacity LAN switching functional and performance testing with broadband access, metropolitan and enterprise routing protocol test capability.
- Spirent TestCenter customers can use the 10GbE test modules to evaluate key feature functional and performance parameters of 10GbE switches, link aggregators and routers under typical or extreme traffic load with deliberate error conditions. The modules compare and validate 10GbE network equipment for compliance to product and protocol specifications prior to deployment.
- These test tools ensure the performance of advanced network device features. Such features encompass total host client capacities and throughput, QoS class prioritization, SLA bandwidth verification, VLAN tagging and dozens of routing protocols, scalability protocols and performance metrics. The 10GbE test modules are routinely used to verify routing controls and converged network capabilities.







#### **FEATURES & BENEFITS**

- New 10GBASE-T: 10GBASE-T is the latest data center solution for interconnecting switches, servers and routers. It can test and characterize 10Gbps communication over shielded/unshielded twisted pair (UTP) copper according to the 802.3an standard, including connectivity up to 100m on CAT6A and CAT7 copper cables. The standard specifies a short reach mode of 55 meters and a standard reach of 100 meters of CAT6A Class E, Class F and Augmented E (EA) cabling. Note that CX4 copper cabling is limited to 15 meters in reach distance and 10GBASE-T overcomes this limitation by reaching up to 100 meters.
  - Benefit: 10GBASE-T operates in 10GbE LAN mode over Cat6A copper cable which is less expensive and easier to install compared to10GBASE-CX4 copper cables and connector systems. It also allows NEMs to build higher density switches and routers. Over time, as the power consumption of the PHY goes down, 10GBASE-T will become a high port density interface.
- Spirent TestCenter 10GbE test tools are uniquely featured to measure ultra-low latency (down to 10 nanosecond resolution) in these challenging tests, in any topology and with a high degree of realistic network traffic. Testing silicon communications chips and optical transceivers is vital. This is due to significant increases in chip-based functionality, high port density and scalability combined with ultra-low forwarding latency, all at 10GbE line rates (e.g. less than 2 microseconds for 64-byte packets).
- Spirent leads the industry with the highest accuracy 10GbE latency measurement available:
  - Qualified accuracy at all Ethernet speeds
  - Measure with 10 nanosecond resolution and excellent repeatability at all Ethernet speeds
  - Measure latency in any topology and in multiple speed tests: GigE to 10GbE
  - Unlike Spirent's competitors, Spirent's 10GbE requires no post-test results correction
- Increased equipment utilization with hot swappable XENPAK/CX4, X2,XFP and 10GBASE-T network media interfaces.

Up to 24 ports of 10GbE are supported in a 9U rack-mount unit chassis, and up to 4 ports are supported in the portable chassis. Improve test case throughput: Two test engineers may independently run tests on a 2-port, 10GbE Multiple MSA test module.

### **TECHNICAL SPECIFICATIONS**

- Support for Deficit Idle Count (DIC), Link Fault Signaling (LFS), loop line timing, Ethernet preamble editing, Management Data Input/Output (MDIO) and diagnostic loopback
- The RFC 2544 and 2889 test package software options allow the user to rapidly set up and execute tests using industry standard test methodologies
- Traffic wizards allow easy setup of unicast, multicast, RFC-based tests, VLAN tagged, IPv4 and IPv6 test configurations
- Adjust traffic loads in real time and see the affect on the device under test with Spirent TestCenter's real time graphical and statistics reports
- Prioritized scheduling mode allows users to mix constant and bursty traffic on the same port and precisely schedule high priority flows to minimize jitter and other performance parameters
- Critical protocols such as spanning tree, VLAN, DHCP, IGMP, PPP, MPLS, QoS and IPTV are fully integrated, and the system supports a broad selection of unicast and multicast routing protocols
- A graphically driven frame editor allows the user to select from a wide variety of preconfigured frame templates to edit standard fields and to create custom control and data plane packets without manual byte offset calculations
- Concurrently runs advanced measurements in real time such as jitter, packet loss, sequencing, latency and data integrity using PRBS techniques
- An interactive feature allows functional and negative testing, including group join and prune messages, start/stop hellos and start/stop router emulation
- The analyzer supports a combination of 5 HyperFilters<sup>™</sup>, four 16-bit and one 32-bit that operate on the incoming traffic stream
- Up to 65,535 streams or sub-streams can be analyzed on a single port
- All port counters are 64-bits wide, can be charted and are available in real time

## High Density 10-Gigabit Ethernet Test Module Specifications

Feature	MSA-1001B	MSA-2001B
Personality Board Types (interchangeable, 1-port)	<ul> <li>For XENPAK select part number XEN-4001A</li> <li>For X2 select part number XTO-4001A</li> <li>For XFP select part number XFP-4001A</li> <li>For 10GBASE-T select part number GBT-4001A</li> </ul>	
Optical Transceiver Types	<ul> <li>XENPAK offers LAN only, or LAN and WAN support</li> <li>X2 offers LAN only support</li> <li>XFP offers LAN and WAN support</li> </ul>	
Laser Wavelengths	<ul> <li>XENPAK and XFP: 850nm, 1310nm, 1550nm</li> <li>X2: 850nm, 1310nm</li> </ul>	
Copper Transceiver Type	XENPAK format for 10GBASE-CX4	
10GbE IEEE 802.3ae Protocol Modes	Serial LAN and WAN	
Optical Cabling	Multi-mode fiber, single mode fiber	
Copper Cabling	IEEE-compliant 10GBASE-CX4 3ft/1m, 15ft/4m, or 45ft/15m IEEE – TIA-155 Compliant 10GBASE-T CAT6A UTP 3m, CAT6A Shielded 3m	
Signal Rate	10.3125 Gbps LAN or 9.58464 Gbps WAN	
CPU Memory	512MB*	1GB
Maximum Transmit Streams	16,384 per port	32,767 per port
Total Number of Variable Fields per Stream (VFD)	4	6
Maximum Receive Streams	65,535 per port	
Minimum/Maximum Frame Size (w/o CRC)	48-16,367 Bytes	48-16,367 Bytes
Minimum/Maximum Transmit Rates	1 packet per 2.14 seconds to 104% of line rate	
Timestamp Resolution	10 nanoseconds	
Latency Measurement Accuracy and Repeatability	Accuracy depends on transceiver technology and the manufacturer. Please consult Spirent for additional information.	
Loop Line Timing	Transmit test traffic at the DUT's clock rate/Selectable supported on XFP-4001A	
Deficit Idle Count Support	LAN and WAN modes/ON or OFF selectable	
Link Fault Signaling	LAN and WAN modes/ON or OFF selectable	

\*Note: Requires Spirent TestCenter v2.15 or higher applications software

#### SYSTEM REQUIREMENTS

# Minimum PC, UNIX or Linux Requirements by System Size

For Small Port System (2-25 ports)

Minimum Requirement – 2.4 GHz Intel Pentium 4 processor (or equivalent), 512 MB RAM and 10 GB of free disk space

Recommended System – Intel Core™ 2 Duo E6300 processor (or equivalent), 2 GB of free RAM and 10 GB of free disk space

For Medium Port System (26-75 ports)
 Minimum Requirement – 3 GHz Intel
 Pentium 4 processor (or equivalent), 2 GB
 of free RAM, 15 GB of free disk space

Recommended System – Intel Core 2 Duo E6400 processor (or equivalent), 4 GB free RAM, 100 GB of free disk space

For Large System (76 ports and above)

Minimum Requirement – Intel Core 2 Duo E6400 processor (or equivalent), 3 GB free RAM, 100 GB free space on hard drive

Recommended System – Intel Core 2 Duo E6600 processor (or equivalent), 4 GB of RAM, 100 GB of free disk space

#### Spirent TestCenter Hardware Requirements

 Pentium® or greater PC running Windows® XP Professional SP2 with mouse/color monitor required for GUI operation (See Minimum PC Requirements section)

### Spirent TestCenter 10-GIGABIT ETHERNET MULTIPLE MSA ETHERNET TEST SOLUTION

- One Ethernet cable and one 10/100/1000Mbps Ethernet card installed in the PC A SPT-2000A Spirent 2U Chassis and Controller, SPT-5000A Spirent 5U Chassis and Controller or SPT-9000A Spirent 9U Chassis and Controller
- Operating system languages supported: English, French, German, Italian, Japanese, Korean and Chinese (traditional and simplified)
- Operating systems supported: Windows XP SP2, Windows 2003 Server (32 bit and 64 bit), RedHat EL3 and EL5, Solaris 8.0 and 10.0

#### **ORDERING INFORMATION**

Description	Part Number		
10GbE Multi-MSA Module, 2-Port, Single Slot	MSA-1001B		
10GbE Multi-MSA Module, 2-Port, Single Slot	MSA-2001B		
XENPAK LAN/WAN Personality Board per port	XEN-4001A		
X2 LAN/WAN Personality Board per port	XTO-4001A		
XFP LAN/WAN Personality Board	XFP-4001A		
10GBASE-T Personality Board	GBT-4001A		
XENPAK MSA Optical Transceivers			
1310nm, Single Mode, 10GBASE-LR	ACC-6022A		
1550nm, Single Mode, 10GBASE-ER	ACC-6023A		
850nm, Multi-Mode, 10GBASE-SR	ACC-6023A		
850nm, Multi-Mode, 10GBASE-SR	ACC-6024A		
1310nm, Single Mode, LAN-WAN, 10GBASE-LR/LW	ACC-6028A		
X2 MSA Optical Transceivers Note: X2 transceivers only support the 10GbE LAN mode			
850nm, Multi-Mode, 10GBASE-SR	ACC-6042A		
1310nm, Single Mode, 10GBASE-LR	ACC-6043A		
XFP MSA Optical Transceivers (with 10GbE LAN/WAN support)			
850nm, Multi-Mode, 10GBASE-SR/SW	ACC-6030A		
1310nm, Single Mode, 10GBASE-LR/LW	ACC-6031A		
1550nm, Single Mode, 10GBASE-ER/EW	ACC-6032A		
<b>10-Gigabit Ethernet over Copper</b> Note: 10GBASE-CX4 only supports the 10GbE LAN mode			
10GBASE-CX4 in the XENPAK Transceiver format	ACC-6033A		
Cable, CX4 Transceiver, 3ft/1m	ACC-3412A		
Cable, CX4 Transceiver, 15ft/3m	ACC-3410A		
Cable, CX4 Transceiver, 45ft/15m	ACC-3411A		
10GBASE-T Qualified Cables			
Cable, 10GBASE-T CAT6A (Augmented) shielded STP cable, 3m	ACC-0011A		
Cable, 10GBASE-T CAT6A (Augmented) 3-meter UTP cable, 3m	ACC-0010A		



Spirent Communications 1325 Borregas Avenue Sunnyvale, CA 94089 USA

SALES AND INFORMATION sales@spirent.com www.spirent.com

Americas T: +1 800.SPIRENT +818 676.2683

Europe, Middle East, Africa T: +33 1 6137.2250

**Asia Pacific** T: +852 2511.3822

© 2008 Spirent Communications, Inc. All of the company names and/or brand names and/or product names referred to in this document, in particular the name "Spirent" and its logo device, are either registered trademarks or trademarks pending registration in accordance with relevant national laws. All rights reserved. Specifications subject to change without notice. Rev. E 01/08