

ABN 43 064 478 842

231 osborne avenue clayton south, vic 3169
PO box 1548, clayton south, vic 3169
t 03 9265 7400 f 03 9558 0875
freecall 1800 680 680
www.tmgtestequipment.com.au

Test & Measurement

Complimentary Reference Material

sales
rentals
calibration
repair
disposal
This PDF has been made available as a complimentary service for you to assist in evaluating this model for your testing requirements.
TMG offers a wide range of test equipment solutions, from renting short to long term, buying refurbished and purchasing new. Financing options, such as Financial Rental, and Leasing are also available on application.
TMG will assist if you are unsure whether this model will suit your requirements.
Call TMG if you need to organise repair and/or calibrate your unit.
If you click on the "Click-to-Call" logo below, you can all us for FREE!



Disclaimer:

All trademarks appearing within this PDF are trademarks of their respective owners.



18 GHz 100 Ω Differential Impedance TDR Hand Probes

P80318 • P80318X



P80318

The P80318 is an 18 GHz 100 Ω input impedance differential TDR hand probe. This probe enables high fidelity impedance measurements of differential transmission lines. The adjustable probe pitch enables a wide variety of differential line spacing and impedances. The P80318 probe also includes two precision SMA cables with parallel control lines that provide the 80A02 the control for EOS/ESD protection.

P80318X

The P80318X is designed for high volume PCB impedance test applications. These applications require maximum manufacturing up-time. The P80318X includes everything in a P80318 plus a second probe body for use if the first probe body needs to be serviced due to normal wear. The P80318 probe can be used as a stand alone high resolution probe, but it is specially designed to be used with two 80A02 EOS/ESD Protection Modules. To maximize testing up-time and minimize repair costs, protecting the sampling module from static damage is a requirement. Damage to the sampling module is typically due to electro-overstress (EOS) and electrostatic discharge (ESD) from large static charges stored in the DUT. Use of two 80A02 modules ensures proper probe grounding prior to switching signal to the sampling module.

Features & Benefits

18 GHz Bandwidth

Direct In Circuit TDR Testing

Reliable and Repeatable Resolution of Impedance Variations to 0.12"

Adjustable Probe Pitch from 0.5 mm to 4.2 mm

Probing of Fully Balanced Differential Signals Without Ground Contact

Double Cushioning Design Enables Probe Tips to Maintain Proper DUT Contact

Protects Sampling Module from Static Damage when Used with Two 80A02 Modules

Applications

Circuit Board Controlled Impedance Testing (TDR)

Loss Tangent Measurements for Differential Transmission Lines

Failure Analysis of PCB with or without Components Mounted

Package Impedance Testing (TDR)



18 GHz 100 Ω Differential Impedance TDR Hand Probes

P80318 • P80318X

Characteristics

Nominal Length with Cable – 1 meter. Attenuation – 1X. Probe Only Bandwidth – >20 GHz. Probe Pitch – 0.5 to 4.2 mm (signal tip to signal tip). Connector Type – SMA. Measured Reflected TDR Fall Time – <39 ps. Impedance – 50 Ω odd mode, 100 Ω differential. Max V_{in} – 5.0 V. Probe Only Propagation Delay – 1.0 ns typical. TDR Control Activation Force – 150 to 200 grams each probe half. (Note: numeric values shown are typical).

Ordering Information

P80318

18 GHz 100 Ω Differential TDR Hand Probe.

Includes: 18 GHz bandwidth 50 Ω odd mode input impedance (100 Ω differential impedance), differential passive handheld probe with one set of two precision SMA cables, soft storage case, user manual and three replaceable ground shorting straps.

P80318X

18 GHz 100 Ω Differential TDR Hand Probe for Manufacturing.

Includes: Two 18 GHz bandwidth 50 Ω odd mode input impedance (100 Ω differential impedance), differential passive handheld probes with one set of two precision SMA cables, soft storage case, user manual and three replaceable ground shorting straps. Second probe body is provided as a back-up to the first to maximize manufacturing up-time if the first probe body needs to be serviced due to wear.

Recommended Accessories

 $\mbox{P8018}$ – 18 GHz Single-Ended 50 Ω TDR Probe. To compliment TDR probing for single ended applications.

80A02 - ESD/EOS TDR protection module.

External Probe Power Cable – To reduce module acquisition slot consumption, the 80A02 modules can run off this probe power cable (p/n 174-3896-00).

Ground Spring Kit – Set of two ground springs with a spare set screw for P80318 probe (p/n 020-2670-00).

ASEAN / Australasia / Pakistan (65) 6356 3900 Austria +41 52 675 3777 Balkan, Israel, South Africa and other ISE Countries +41 52 675 3777 Belaium 07 81 60166 Brazil & South America 55 (11) 3741-8360 Canada 1 (800) 661-5625 Central East Europe, Ukraine and the Baltics +41 52 675 3777 Central Europe & Greece +41 52 675 3777 Denmark +45 80 88 1401 Finland +41 52 675 3777 France & North Africa +33 (0) 1 69 86 81 81 Germany +49 (221) 94 77 400 Hong Kong (852) 2585-6688 India (91) 80-22275577 Italy +39 (02) 25086 1 Japan 81 (3) 6714-3010 Luxembourg +44 (0) 1344 392400 Mexico, Central America & Caribbean 52 (55) 56666-333 Middle East, Asia and North Africa +41 52 675 3777 The Netherlands 090 02 021797 Norway 800 16098 People's Republic of China 86 (10) 6235 1230 Poland +41 52 675 3777 Portugal 80 08 12370 Republic of Korea 82 (2) 528-5299 Russia & CIS 7 095 775 1064 South Africa +27 11 254 8360 Spain (+34) 901 988 054 Sweden 020 08 80371 Switzerland +41 52 675 3777 Taiwan 886 (2) 2722-9622 United Kingdom & Eire +44 (0) 1344 392400 USA 1 (800) 426-2200 For other areas contact Tektronix, Inc. at: 1 (503) 627-7111 Updated 15 June 2005

> Our most up-to-date product information is available at: www.tektronix.com

\$

Copyright © 2005, Tektronix, Inc. All rights reserved. Tektronix products are covered by U.S. and foreign patents, issued and pending. Information in this publication supersedes that in all previously published material. Specification and price change privileges reserved. TEKTRONIX and TEK are registered trademarks of Tektronix, Inc. All other trade names referenced are the service marks, trademarks or registered trademarks of their respective companies.

6/05 DV/WOW

85W-18863-1



Contact Tektronix: