



ABN 43 064 478 842

➤ 231 osborne avenue clayton south, vic 3169
PO box 1548, clayton south, vic 3169
t 03 9265 7400 f 03 9558 0875
freecall 1800 680 680
www.tmgtestequipment.com.au

Test & Measurement

- sales
- rentals
- calibration
- repair
- disposal

Complimentary Reference Material

This PDF has been made available as a complimentary service for you to assist in evaluating this model for your testing requirements.

TMG offers a wide range of test equipment solutions, from renting short to long term, buying refurbished and purchasing new. Financing options, such as Financial Rental, and Leasing are also available on application.

TMG will assist if you are unsure whether this model will suit your requirements.

Call TMG if you need to organise repair and/or calibrate your unit.

If you click on the “Click-to-Call” logo below, you can call us for FREE!

TMG Corporate Website

TMG Products Website



Click-to-Call
TMG Now



Disclaimer:

All trademarks appearing within this PDF are trademarks of their respective owners.



1.5 GHz Active Probe

► TAP1500



TAP1500 Single-ended Active FET Probe provides excellent high-speed electrical and mechanical performance required for today's digital system designs. Specifically designed for use and direct connection to the TekVPI probe interface used on Tektronix' new DPO7000 and DPO4000 Series oscilloscopes, the TAP1500 Active FET Probe achieves high-speed signal acquisition and measurement fidelity by solving three traditional problems:

- Lower DUT loading effects with ≤ 1 pF input capacitance and $1\text{ M}\Omega$ input resistance
- Versatile DUT connectivity for attaching to small SMDs
- Preserves oscilloscope bandwidth at the probe tip for DPO7000 and DPO4000 Series Oscilloscope models, up to 1 GHz

► Characteristics

Bandwidth (probe only) – ≥ 1.5 GHz.
Attenuation (probe only) – $10\times \pm 2\%$.
Rise Time (probe only) – ≤ 267 ps.
Input Capacitance – < 1 pF.
Input Resistance – $1\text{ M}\Omega$.
Linear Dynamic Range – $\pm 8\text{ V}$ ($16\text{ V}_{\text{p-p}}$).
Input Offset Range – $\pm 10\text{ V}$.
Max Input Voltage (Non-destruct) – $\pm 15\text{ V}$ (DC + pkAC).
Propagation Delay – 5.3 ns.

Physical Characteristics

Probe Head Size	mm	in.
Height	11.25	0.44
Width	5.1	0.20
Length	60.4	2.38
Weight	kg	lbs.
Net	0.45	1
Other Dimensions		
Cable Length	1300	51

Power Requirements

TAP1500 is powered directly by the DPO7000 and DPO4000 Series Oscilloscopes using TekVPI probe interface.

Recommended Oscilloscopes
DPO7000 and DPO4000 Series Oscilloscopes with TekVPI probe interface.

Environmental

Temperature –

Operating: 0°C to $+50^\circ\text{C}$.

Non-Operating: -40°C to $+71^\circ\text{C}$.

Humidity –

Operating: 5% to 95% Relative Humidity (RH) at up to $+30^\circ\text{C}$; 5% to 85% RH above $+30^\circ\text{C}$ up to $+50^\circ\text{C}$; non-condensing.

Non-operating: 5% to 95% Relative Humidity (RH) at up to $+30^\circ\text{C}$; 5% to 85% RH above $+30^\circ\text{C}$ up to $+75^\circ\text{C}$; non-condensing.

Altitude –

Operating: Up to 3,000 m (10,000 feet).

Non-operating: Up to 15,240 m (50,000 feet).

Regulatory

Compliance Labeling – WEEE (European Union).

Standard Warranty

One year parts and labor.

► Features & Benefits

Outstanding Electrical Performance

- ≥ 1.5 GHz Probe Bandwidth
- < 267 ps Rise Time
- ≤ 1 pF Input Capacitance
- $1\text{ M}\Omega$ Input Resistance
- -8 V to $+8\text{ V}$ Input Dynamic Range
- -10 V to $+10\text{ V}$ DC Input Offset Range

Versatile Mechanical Performance

- Small Compact Probe Head for Probing Small Geometry Circuit Elements
- DUT Attachment Accessories Enable Connection to SMDs As Small As 0.5 mm Pitch
- Robust Design for Reliability

Easy to Use

- Connects Directly to DPO7000 and DPO4000 Series Oscilloscopes Using the New TekVPI™ Probe Interface
- Provides Automatic Units Scaling and Readout on the Oscilloscope Display
- Easy Access to Oscilloscope Probe Menu Display for Probe Status/Diagnostic Information, and to Control Probe DC Offset

► Applications

High-speed Digital Systems Design

Component Design and Characterization

Manufacturing Engineering and Test

Educational Research

Signals with Voltage Swings Up to $16\text{ V}_{\text{p-p}}$

1.5 GHz Active Probe

► TAP1500

► Ordering Information

TAP1500

1.5 GHz Active Probe.

► Standard Accessories Included

Description	Quantity with TAP1500	Reorder Part Number
Low Inductance 1 in. Z-Ground Lead	2 each	196-3439-xx
3 in. Ground Lead	2 each	196-3437-xx
6 in. Ground Lead	2 each	196-3436-xx
Y-Lead Adapter	2 each	196-3463-xx
Color Coding Clips	2 each of 5 colors	016-1315-xx
Solderable Probe Tips	10 each	131-5638-xx
SMT KlipChip™ Adapter	4 each	206-0364-xx
Right Angle Square Pin Adapter	2 each	214-4227-xx
100 mm Square Pin Ground Adapter	2 each	131-5777-xx
User Manual ^{*1}	1 each	071-1809-xx English or 071-1810-xx Japanese or 071-1811-xx Simplified Chinese
Nylon Carrying Case	1 each	016-1952-xx

^{*1} Manual language must be specified when ordering.

Manual Options

Opt. L5 – Japanese instruction manual.

Opt. L7 – Simplified Chinese instruction manual.

Service Options

Opt. C3 – Calibration Service 3 Years.

Opt. C5 – Calibration Service 5 Years.

Opt. D1 – Calibration Data Report.

Opt. D3 – Calibration Data Report 3 Years
(with Opt. C3).

Opt. D5 – Calibration Data Report 5 Years
(with Opt. C5).

Opt. R3 – Repair Service 3 Years.

Opt. R5 – Repair Service 5 Years.

Recommended Accessories

Description	Package Quantity	Reorder Part Number
50 mm IC Adapter	12	SF501
25 mm IC Adapter	12	SF502
0.5 mm IC Adapter	12	SF503
SMT KlipChip Adapter	20	SMG50
IC Micro-Grabber	2	013-0309-00

Contact Tektronix:

ASEAN / Australasia / Pakistan (65) 6356 3900

Austria +41 52 675 3777

Balkan, Israel, South Africa and other ISE Countries +41 52 675 3777

Belgium 07 81 60166

Brazil & South America 55 (11) 3741-8360

Canada 1 (800) 661-5625

Central East Europe, Ukraine and the Baltics +41 52 675 3777

Central Europe & Greece +41 52 675 3777

Denmark +45 80 88 1401

Finland +41 52 675 3777

France & North Africa +33 (0) 1 69 86 81 81

Germany +49 (221) 94 77 400

Hong Kong (852) 2585-6688

India (91) 80-22275577

Italy +39 (02) 25086 1

Japan 81 (3) 6714-3010

Luxembourg +44 (0) 1344 392400

Mexico, Central America & Caribbean 52 (55) 56666-333

Middle East, Asia and North Africa +41 52 675 3777

The Netherlands 090 02 021797

Norway 800 16098

People's Republic of China 86 (10) 6235 1230

Poland +41 52 675 3777

Portugal 80 08 12370

Republic of Korea 82 (2) 528-5299

Russia & CIS 7 095 775 1064

South Africa +27 11 254 8360

Spain (+34) 901 988 054

Sweden 020 08 80371

Switzerland +41 52 675 3777

Taiwan 886 (2) 2722-9622

United Kingdom & Eire +44 (0) 1344 392400

USA 1 (800) 426-2200

For other areas contact Tektronix, Inc. at: 1 (503) 627-7111

Updated 15 June 2005

Our most up-to-date product information is available at:
www.tektronix.com

Product(s) are manufactured
in ISO registered facilities.



Copyright © 2005, Tektronix, Inc. All rights reserved. Tektronix products are covered by U.S. and foreign patents, issued and pending. Information in this publication supersedes that in all previously published material. Specification and price change privileges reserved. TEKTRONIX and TEK are registered trademarks of Tektronix, Inc. All other trade names referenced are the service marks, trademarks or registered trademarks of their respective companies.

12/05 HB/WWW

51W-19043-1

Tektronix
Enabling Innovation