

ABN 43 064 478 842

231 osborne avenue clayton south, vic 3169 PO box 1548, clayton south, vic 3169 t 03 9265 7400 f 03 9558 0875 freecall 1800 680 680

www.tmgtestequipment.com.au

Test & Measurement

- sales
- rentals
- calibration
- repair
- disposal

Complimentary Reference Material


This PDF has been made available as a complimentary service for you to assist in evaluating this model for your testing requirements.

TMG offers a wide range of test equipment solutions, from renting short to long term, buying refurbished and purchasing new. Financing options, such as Financial Rental, and Leasing are also available on application.

TMG will assist if you are unsure whether this model will suit your requirements.

Call TMG if you need to organise repair and/or calibrate your unit.

If you click on the "Click-to-Call" logo below, you can all us for FREE!



Disclaimer:

All trademarks appearing within this PDF are trademarks of their respective owners.







DC - 4.0 GHz 50 WATTS





Designed to comply with MIL-DTL-39030

Natural Convection Cooling

Specifications

Nominal Impedance: 50 ohms

Frequency Range: DC - 4.0 GHz

Power: 50W CW average to 25°C; de-rated linearly to 2.5 W at 125°C. Peak power of 5KW;


5µsec pulse width; 0.5% duty cycle.

Temperature Range: -55°C to 125°C

Construction: Black aluminum alloy body with

passivated stainless steel connectors.

Connectors: Type N, SMA, or DIN 7/16; stainless steel M/F connectors per MIL-STD-348A, interface dimensions mate nondestructively with MIL-PRF-39012.



Calibration: VSWR performed across frequency range. Calibration test data available at additional cost.

Maximum VSWR:

Frequency (GHz)	VSWR
DC - 4.0	1.20

Weight: .28 kg/10 oz.

Physical Dimensions:

Length:

Connector Type	DIM "A"
Type N Female –3	90.17 (3.55)
Type N Male –4	96.98 (3.818)
SMA Female –1	85.80 (3.378)
SMA Male –2	89.76 (3.534)

Note: Dimensions are given in mm (inches) and are maximum, unless otherwise specified.



WEB: http://www.WeinschelAssociates.com EMAIL: sales@WeinschelAssociates.com