



ABN 43 064 478 842

➤ 231 osborne avenue clayton south, vic 3169  
PO box 1548, clayton south, vic 3169  
t 03 9265 7400 f 03 9558 0875  
freecall 1800 680 680  
[www.tmgtestequipment.com.au](http://www.tmgtestequipment.com.au)

## Test & Measurement

- sales
- rentals
- calibration
- repair
- disposal

## Complimentary Reference Material

This PDF has been made available as a complimentary service for you to assist in evaluating this model for your testing requirements.

TMG offers a wide range of test equipment solutions, from renting short to long term, buying refurbished and purchasing new. Financing options, such as Financial Rental, and Leasing are also available on application.


TMG will assist if you are unsure whether this model will suit your requirements.

Call TMG if you need to organise repair and/or calibrate your unit.

If you click on the "Click-to-Call" logo below, you can call us for FREE!

TMG Corporate Website

TMG Products Website



### Disclaimer:


All trademarks appearing within this PDF are trademarks of their respective owners.

# TERMINATION

# MODEL WA1446

DC –18.0 GHz

25 WATTS



## Features

Type N or SMA stainless steel M or F connectors per MIL-STD-348A, interface dimensions mate nondestructively with MIL-PRF-39012. Designed to meet MIL-A-3933 environmental specifications.

## Specifications

**Nominal Impedance:** 50 ohms

**Frequency Range:** DC -18.0 GHz

**Power Rating:** 25W CW/ 1 KW peak. Maximum rated average power to 25°C ambient temperature, de-rated linearly to 10 watts at 125°C. 1 kilowatt peak (5 µsec pulse width; 5% duty cycle).

**Temperature Range:** -55°C to +125°C

**Construction:** Black finned aluminum alloy body with passivated stainless steel connector. Gold plated beryllium copper female contact.

**Calibration:** VSWR performed across frequency range. Calibration test data available at additional cost.

## Maximum VSWR

GHz	VSWR
DC – 8.0	1.20
8.0 – 12.4	1.25
12.4 – 18.0	1.35

## Weight: (Max)

Type N	0.18 kg/ 6 oz.
SMA	0.12 kg/ 4 oz.

## Physical Dimensions:

### Length:

Connector	Dimension A
Type N male	81.53 (3.21)
Type N female	82.30 (3.24)
SMA male	87.38 (3.44)
SMA female	84.07 (3.31)

**Diameter:** 41.40 (1.63)

Note: Dimensions are given in mm (inches) and are maximum, unless otherwise specified



## WEINSCHTEL ASSOCIATES

TEL: 877.948.8342 / 301.963.4630 ♦ Fax: 301.963.8640

WEB: <http://www.WeinschelAssociates.com>

EMAIL: [sales@WeinschelAssociates.com](mailto:sales@WeinschelAssociates.com)

102

Specification  
Subject to change  
without notice