



ABN 43 064 478 842

231 Osborne Avenue Clayton South, VIC 3169
PO Box 1548, Clayton South, VIC 3169
t 03 9265 7400 f 03 9558 0875
freecall 1800 680 680
www.tmgtestequipment.com.au

Test & Measurement

- > sales
- > rentals
- > calibration
- > repair
- > disposal

Complimentary Reference Material

This PDF has been made available as a complimentary service for you to assist in evaluating this model for your testing requirements.

TMG offers a wide range of test equipment solutions, from renting short to long term, buying refurbished and purchasing new. Financing options, such as Financial Rental, and Leasing are also available on application.

TMG will assist if you are unsure whether this model will suit your requirements.

Call TMG if you need to organise repair and/or calibrate your unit.


If you click on the "Click-to-Call" logo below, you can call us for FREE!

TMG Corporate Website

TMG Products Website



Click-to-Call
TMG Now



Product Lifecycle Management System

Disclaimer:

All trademarks appearing within this PDF are trademarks of their respective owners.





Fixed Coaxial Attenuator High Power

MODEL WA68

DC – 6.0 GHz

100 WATTS



Features

Type N, DIN 7/16 or SMA stainless steel M/F connectors per MIL-STD-348A, interface dimensions mate nondestructively with MIL-PRF-39012. Designed to meet MIL-DTL-3933 environmental specification. Unit may be mounted in any position. Mounting holes provided on bottom of unit.

Specifications

Nominal Impedance: 50 ohms.

Frequency Range: DC - 6.0 GHz.

Nominal dB Values: 1 - 30 dB.

Power Sensitivity: < 0.0005 dB/dB/W;
Unidirectional in power.

Power Rating: 100 watts average. Maximum rated average power to 25°C ambient temperature, derated linearly to 10 watts at 125°C. 10 kilowatt peak (5 µsec pulse width; 0.5% duty cycle).

Temperature Range: -55°C to +125°C.

Temperature Coefficient: < 0.0004 dB/dB/°C.

Standard Nominal Values and Deviations:

Attenuation (dB)	Accuracy ± dB
	DC - 6.0 GHz
1,2	1.20
3,6,10,20,30	1.25

Construction: Black aluminum alloy body with passivated stainless steel connectors. Gold plated beryllium copper contacts.

Calibration: Insertion Loss and VSWR performed across frequency range. Calibration test data available at additional cost.

Maximum VSWR:

Frequency (GHz)	VSWR
DC – 6.0	1.30

Weight:

Type N	1.5 kg/ 3.3 lb.
DIN 7/16	1.7 kg/ 3.7 lb.

Physical Dimensions:

Length:

Connector	Length
Type N	112.1 (4.4)
DIN 7/16	139.7 (5.5)

Width: 89.0 (3.5).

Height: 54.0 (2.1).

Note: Dimensions are given in mm (inches) and are maximum, unless otherwise specified.



WEINSCHTEL ASSOCIATES

TEL: 877.948.8342 / 301.963.4630 ♦ Fax: 301.963.8640

WEB: <http://www.WeinschelAssociates.com>

EMAIL: sales@WeinschelAssociates.com

59

Specification
Subject to change
without notice