



Honeywell

We understand commitment to safety.

***You rely on your workers to get the job done
and they count on you to keep them safe.***



Industry Best Pricing



Finance Available



Short to Medium Project-Based Rental Solutions



Dedicated Technical & After-Sales Support



In-house Diagnostics, Repair & NATA Calibration Laboratory



FREECALL 1800 680 680

Honeywell
THE POWER OF CONNECTED

MILLER

**HOWARD
LEIGHT**



This reference material is provided by TMG Test Equipment, a Honeywell Certified Service Agent and Channel Partner



**Honeywell Miller new Durahoist 3Pod
for confined spaces**

DuraHoist 3Pod: A single tripod adjustable to various confined space work situations. It is easy to transport and rapid to install.

- Easy to carry & move (leg profile ergonomic for hand grip)
- Easy & safe to install in less than 2 minutes (all legs open simultaneously, 1 knob fixing all legs together)
- Adaptable to different manhole sizes (1m – 1.50m – 2.50m)
- Certified to the last requirements of the EN 795:2012 class B (CN/TS 16415)
- Tested for 2 persons (up to 140kg each)



1m



1.50m



2.50m with webbing strap

What's a fall arrest system for confined spaces?


- 1 ANCHORAGE STRUCTURE**
Fall arrest system compliant to EN795:2012 B
- 2 WINCH**
Lifting load disposal. Machine Directive 2006/42/CEE
- 3 SELF RETRACTING LIFELINE WITH RETRIEVAL WINCH**
Compliant to EN 360:2002 and EN 1496:2006
- 4 SAFETY HARNESS**
Compliant to EN 361:2002



FEATURES AND BENEFITS

UNIQUE OPENING/FIXATION MECHANISM PLACED IN THE HEAD OF THE TRIPOD


- + Improved productivity
- + Fast adjusting and locking system for different leg opening angles (at 1m - 1.50m - 2.50m adapted to any manhole)
- + Number of attachment point on the head (3 holes + 1 eye-swivel)



PATENT PENDING

AVAILABLE TO ATTACH UP TO 2 PERSONS

and each weighing up to 140kg



ADJUSTABLE LEGS

- + End-stop leg at maximum length
- + Engraved marking for easy leg height adjustment (visual marking to position pin in hole)
- + Safe locking pin

ROBUST LEG DESIGN

- + Ergonomic leg's profile for hand grip
- + Resistant legs
- + Improved rescue when victim is pulled over to the side

EASY & QUICK CONNECTION BRACKETS FOR RAPID INSTALLATION OF ACCESSORIES ON OUTSIDE TRIPOD LEG:

- + Rescuing device to stop the fall and rescue the person
- + Winch for lifting loads (Maximal weight load limit 300kg)

LIGHTWEIGHT MATERIAL

- + Aluminium lightweight (16kg) and durable

STABILITY

- + Durable foot sole
- + Good stability and maximum slip resistance to all ground surfaces

PATENT PENDING

When closed, the legs are fixed and the tripod can be easily transported by gripping just one leg.



1.45m when closed for easy transport in small vehicles.

Specially designed for:

- Water Utilities (sewer lines, pumping & treatment station)
- Oil & Gas
- Electrical & Telecom companies
- Food and Chemical industries

Technical data sheet

DURAHOIST 3POD Tripod ref 1034430

Description :

A single 3Pod solution adjusted to various confined space work situations which is easy to transport and rapid to install.

Adapted to any manholes from 1m, 1m50 to 2m50.

Tested for 2 persons (up to 140 kg each) equipped with 4 anchorage points located on its head as well as 2 pulley fixed on the legs.



Features:

Material: aluminium.

4 anchorage points.

Foot sole: rubber piece ribbed (screwed).

Detent pin (diam 10) with metallic attachment sling

Graving identification (laser) marking + **QR code**.

Leg length adjustable: 4 positions every 25cm + laser marking

Unique opening / fixation mechanism placed in the head of the tripod:
all legs open simultaneously, 1 knob fixing all legs together (patented).



3 opening angles (diameter of the circle) : 1,40 m – 1,80 m – 2,90 m

Dimension once fully folded for transport: 1,45 m high.

Red webbing at feet level: only when maximum opening (2,5 m manhole).

Legs length ajustements with :

- End-stop to block leg at maximum length.
- Engrave marking to ease the height adjustment of the leg.

Breaking strength: 12 KN

Weight: 16,5 KG NET

Rapid installation of accessories.

Robust leg design :

- Ergonomic legs profile for better hand grip.
- Leg that resists to fall test without feet webbing when opening at 1m and 1m50



Delivered in it packing with handles: dim. 151,5 x 34,5 x 32 cm

