



Honeywell

We understand commitment to safety.

*You rely on your workers to get the job done
and they count on you to keep them safe.*



Industry Best Pricing



Finance Available



Short to Medium Project-Based Rental Solutions



Dedicated Technical & After-Sales Support



In-house Diagnostics, Repair & NATA Calibration Laboratory



FREECALL 1800 680 680



▶ ▶ ▶ MILLER® MIGHTEVAC™ FALL ARRESTOR

PRODUCT INFORMATION

The MightEvac™ fall arrestor combines the superior performance and reliability of the best-selling MightyLite™ Self-Retracting Lifeline Series with a quick-activating retrieval mechanism for emergency evacuation.

PRODUCT FEATURES

- Promotes quick and easy rescue with a 4:1 mechanical advantage (average speed of 7.6m per minute)
- 1.4kN weight capacity
- For emergency evacuation only
- Corrosion-resistant stainless steel/aluminium components
- Convenient, heavy-duty carrying handle
- Available in galvanised steel cable

APPLICATIONS

- Confined Space applications
- Rescue
- Emergency Retrieval

STANDARDS

- EN360 Approved
- Fully compliant to AS/NZS 1891.3 as a type 2 fall arrest device.



TECHNICAL INFORMATION

Materials

Housing:	Aluminium Alloy, Stainless Steel
Drum:	Aluminium Alloy, Stainless Steel
Mainspring:	Stainless Steel
Brake Pawls:	Stainless Steel
Main Shaft:	Stainless Steel
Bushing:	Ball and Roller Bearing
Snap hook:	Drop Forged Steel

Technical

Max Working Load:	140.62kg
Ultimate Tensile Strength:	16.01kN
Lifeline Tension:	13.3/17.8N
Free Fall Distance:	609.6mm
Deceleration Distance:	1.06m
Arresting Force:	4kN



Bracket for the 3POD Tripod System (1034431)