



ABN 43 064 478 842

231 Osborne Avenue Clayton South, VIC 3169  
PO Box 1548, Clayton South, VIC 3169  
t 03 9265 7400 f 03 9558 0875  
freecall 1800 680 680  
www.tmgtestequipment.com.au

## Test & Measurement

- > sales
- > rentals
- > calibration
- > repair
- > disposal

## Complimentary Reference Material

This PDF has been made available as a complimentary service for you to assist in evaluating this model for your testing requirements.

TMG offers a wide range of test equipment solutions, from renting short to long term, buying refurbished and purchasing new. Financing options, such as Financial Rental, and Leasing are also available on application.

TMG will assist if you are unsure whether this model will suit your requirements.

Call TMG if you need to organise repair and/or calibrate your unit.

If you click on the "Click-to-Call" logo below, you can call us for FREE!

TMG Corporate Website

TMG Products Website



Click-to-Call  
TMG Now



Product Lifecycle Management System

### Disclaimer:

All trademarks appearing within this PDF are trademarks of their respective owners.





## 1140LA POWER AMPLIFIER

1000 Watts of RF Power  
For Industrial, Lab  
& Medical Use,

Featuring;

- 9 KHz – 2 MHz
- Power Measurement
  - o Forward & Reflected
- Solid State Reliability
- Forced Air Cooling



The 1140LA Amplifier is a rugged source of RF power for ultrasonics, induction heating and laser modulation as well as plasma applications. It is a totally solid state solution employing RF DMoS FETs in the power amplification stages, offering simultaneous forward and reverse power readouts, and RS232 port for data collection. The 1140LA reflects E&I's commitment to reliable and robust RF power.

### Flexible Operation:

The 1140LA produces 1000 Watts of quasi linear class AB power over a frequency range of 9 to 2 MHz, with a nominal power gain of 55 dB (+/-1dB). Operation over the entire frequency range is possible without the need for any switching. Operation over 4 MHz is achieved with a lower power gain.

The front panel display provides simultaneous measurements of forward and reflected power as well as the unit's status. The RS232 connector at the rear of the unit can also be used to capture this data and reset the unit should a fault occur.

The E&I 1140LA is a 19" rack mount unit 8U high. It employs an integral power supply capable of operation at 115 or 220 VAC, 50 – 60 Hz. The unit weighs approximately 95 lbs or 45 Kg.



150 Lucius Gordon Drive.  
Rochester, NY 14586  
Tel: (585) 214 0598  
Fax: (585) 214 0580

[WWW.ElectronicsAndInnovation.com](http://WWW.ElectronicsAndInnovation.com)

# 1140LA POWER AMPLIFIER

**Class of Operation**  
Class AB

**Frequency Range**  
9 to 2 MHz

**Rated Power Output**  
1,000 Watts

**Power Gain**  
55 dB nominal

**Gain Flatness**  
+/- 1 dB

**Input Power for Rated Output**  
5 mW or 0.7 dBm

**Input Impedance**  
50  $\Omega$

**Output Impedance**  
50  $\Omega$

**Ruggedness**  
Any load VSWR, any phase from open to Short circuit without damage.

**Front Panel Accuracy**  
+/- 3% (up to 2 MHz)

**Drive Source Requirements**  
Any signal Generator, function Generator or oscillator capable of up to 1.4 Vpp into 50  $\Omega$

**Protection:**

INPUT: unit will withstand up to +16dBm input without damage.

THERMAL: the unit can operate at 45°C ambient. If the internal temperature becomes too high the unit will shut down and an error message will appear on the front panel. The unit may be re-set by cycling the power or from the RS232 input.

MISMATCH: the unit will tolerate any mismatch subject to thermal protection.

**Accessories Supplied**

The unit is supplied with an operations manual and AC line cord.

**Temperature Range**  
0 – 45°C

**Cooling**  
Forced air.

**Weight**  
55 lbs (25 KG)

**Dimensions**  
14 x 16.5 x 18.1 (H x W x D)



150 Lucius Gordon Drive.  
Rochester, NY 14586  
Tel: (585) 214 0598  
Fax: (585) 214 0580

[WWW.ElectronicsAndInnovation.com](http://WWW.ElectronicsAndInnovation.com)