

ABN 43 064 478 842

231 osborne avenue clayton south, vic 3169
PO box 1548, clayton south, vic 3169
t 03 9265 7400 f 03 9558 0875
freecall 1800 680 680

www.tmgtestequipment.com.au

# Test & Measurement

- sales
- rentals
- calibration
- repair
- disposal

## **Complimentary Reference Material**

This PDF has been made available as a complimentary service for you to assist in evaluating this model for your testing requirements.

TMG offers a wide range of test equipment solutions, from renting short to long term, buying refurbished and purchasing new. Financing options, such as Financial Rental, and Leasing are also available on application.

TMG will assist if you are unsure whether this model will suit your requirements.

Call TMG if you need to organise repair and/or calibrate your unit.

If you click on the "Click-to-Call" logo below, you can all us for FREE!

## **TMG Corporate Website TMG Products Website** Leuel 4 Disposal Disposal Click-to-Call TMG Now leuel 5 Review & Leuel 3 Repair Renew Review & Renew Repair Calibration Calibration Recycled Acquisition Leuel 1 Acquisition **Purchase** Lease Solution Centre Rent

### Disclaimer:

All trademarks appearing within this PDF are trademarks of their respective owners.

Product Lifecycle Management System







## GN-6025 Series

## Loss Test Sets



GN-6025 Series instruments are fast and easy-to-use handheld Loss Test Sets designed for attenuation and power throughput measurements on point-to-point fiber optic links. They feature a rugged design, built to withstand the difficult testing environment of fiber optic cable installation and maintenance. Calibrated at five wavelengths (850, 1300, 1310, 1550, and 1625 nm), these instruments are ideal for testing all single-mode and multimode fiber applications. The flexible and easy-to-use design is ideal for any testing application; offering a variety of wavelength and connector options.

#### Features and Benefits

- · Accurate attenuation measurements in minimum time
- High power input capacity enables optical amplifier characterization and CATV measurements
- Combined light source and power meter permit loop-back and dual fiber testing
- Multi-wavelength calibrations provide for L-band characterization
- Automatic wavelength switching minimizes test time and reduces errors
- Storage of up to 900 dual wavelength measurement results
- Rugged and lightweight design



#### Loss Test Sets

	GN-6025/M50	GN-6025/A50	GN-6025C/A50	GN-6025/A60	GN-6025C/A60
Calibrated	850, 1300, 1310,	850, 1300, 1310,	850, 1300, 1310,	850, 1300, 1310,	50, 1300, 1310,
Wavelengths	1550, 1625 nm	1550, 1625 nm	1550, 1625 nm	1550, 1625 nm	1550, 1625 nm
Range	+3 to -66 dBm	+3 to -66 dBm	+20 to -56 dBm	+3 to -66 dBm	+20 to -56 dBm
Accuracy 1,2	±0.2 dBm	±0.2 dBm	±0.2 dBm	±0.2 dBm	±0.2 dBm
Linearity 1	±0.1 dB @	±0.1 dB @	±0.1 dB @	±0.1 dB @	±0.1 dB @
	0 to -65 dBm	0 to -65 dBm	0 to -50 dBm	0 to -65 dBm	0 to -50 dBm
Resolution	0.01 dB/0.1 dB	0.01 dB/0.1 dB	0.01 dB/0.1 dB	0.01 dB/0.1 dB	0.01 dB/0.1 dB
	selectable	selectable	selectable	selectable	selectable
Center Wavelength	850/1300 nm	1310/1550 nm	1310/1550 nm	1550/1625 nm	1550/1625 nm
	±20 nm	±30 nm	±30 nm	±30 nm	±30 nm
Stability (8 hours) <sup>2</sup>	±0.05 dB	±0.05 dB	±0.05 dB	±0.05 dB	±0.05 dB

<sup>&</sup>lt;sup>1</sup> Typical specs at 23° C

#### **Power Meters**

	GN-6025	GN-6025C	
Fiber Type	MM/SM	MM/SM	
Calibrated Wavelengths	850, 1300, 1310, 1550, 1625 nm	850, 1300, 1310, 1550, 1625 nm	
Range	+3 to -66 dBm	+20 to -56 dBm	
Accuracy1,2	±0.2 dBm	±0.2 dBm	
Linearity1	±0.1 dB @ 0 to -65 dBm	±0.1 dB @ 0 to -50 dBm	
Resolution	0.01 dB/0.1 dB Selectable	0.01 dB/0.1 dB Selectable	

<sup>&</sup>lt;sup>1</sup> Typical specs at 23° C

## Care for your network with NetTest

With products like the GN-6025 Series, NetTest continues to provide the industry with advanced, affordable solutions for all fiber optic testing needs. With our superior customer service and technical support, there's no better company to rely on for outstanding network care. For more information on the GN-6025 Series or any of NetTest's fiber optic testing solutions, contact a NetTest representative today at 1-315-266-5000 or 1-800-443-6154.



Center Green, Building 4 6 Rhoads Drive Utica, NY 13502 + 1-315-797-4449 1-800-443-6154 fax: +1-315-798-4038 www.nettest.com



<sup>&</sup>lt;sup>2</sup> Typical 1310 nm specs at 23° C with -20 dBm power input

<sup>&</sup>lt;sup>2</sup> Typical 1310 nm specs at 23° C with -20 dBm power input