



ABN 43 064 478 842

➤ 231 osborne avenue clayton south, vic 3169
PO box 1548, clayton south, vic 3169
t 03 9265 7400 f 03 9558 0875
freecall 1800 680 680
www.tmgtestequipment.com.au

Test & Measurement

- sales
- rentals
- calibration
- repair
- disposal

Complimentary Reference Material

This PDF has been made available as a complimentary service for you to assist in evaluating this model for your testing requirements.

TMG offers a wide range of test equipment solutions, from renting short to long term, buying refurbished and purchasing new. Financing options, such as Financial Rental, and Leasing are also available on application.

TMG will assist if you are unsure whether this model will suit your requirements.

Call TMG if you need to organise repair and/or calibrate your unit.

If you click on the “Click-to-Call” logo below, you can call us for FREE!

TMG Corporate Website

TMG Products Website



Click-to-Call
TMG Now



Disclaimer:

All trademarks appearing within this PDF are trademarks of their respective owners.



Water Quality Measurement Solutions

Handheld Turbidimeters

Micro/PW

**WHITE LIGHT EPA
ACCEPTED METHOD 180.1**



Micro/TPI

**INFRARED
CONFORMS TO ISO 7027**



- Auto Ranging 0.01 to 1,100 NTU
- Extended Battery Life
- Waterproof
- Completely Self Contained

Designed to provide the ease of portability needed in the field with rugged durability, the MicroTPW / TPI is a necessity for anyone monitoring turbidity on the go. The shock resistant carrying case holds everything necessary for field operation while the instrument itself removes easily to go wherever it is needed. With a resolution of 0.01 NTU and an extended range to 1,100 NTU, the MicroTPW / TPI is a perfect partner for field use. Advanced HF microcircuitry design substantially increases lamp and battery life.

MicroTPW / MicroTPI Handheld Turbidimeter

Specifications

Conformance:	
MicroTPW	USEPA Method 180.1
MicroTPI	ISO 7027
Measurement Range:	Auto-Ranging from 0 - 1100 NTU
Principle of Operation:	Nephelometric
Certification:	CE, Designed to meet IP67 & NEMA 4X
Accuracy: (0-500 NTU)	± 2% of reading or ± 0.01 NTU whichever is greater
(500-1100 NTU)	± 3% of reading
Resolution:	0.01 NTU < 100 NTU 0.1 NTU < 100.0 - 999.9 NTU 1 NTU < 1000 - 1100 NTU
Response Time:	14 seconds
Display:	4 Digit (7 segment) LCD
Light Source:	
MicroTPW	White Light (Tungsten)
MicroTPI	Infrared - LED (860nm)
Power Supply:	4 -AAA Alkaline Batteries (over 5000 tests)
Sample Cells:	15 mL cell 10 mL sample needed
Materials:	
Instrument Case:	ABS - Injection Molded
Carry Case:	High Density Polyethylene blow molded
Shipping Dimensions:	28 x30.5 x 7.6 cm (11" x 12" x 3")
Shipping Weight:	1.22 kg (2.7 lbs)

Ordering Information

Catalog No. Description

20000 **MicroTPW** White Light Portable Handheld Turbidimeter

20008 **MicroTPI** Infrared Portable Handheld Turbidimeter

The **MicroTPW / MicroTPI** includes carrying case, one set of PRIMEIME calibration standards, indexing rings, 4AAA alkaline batteries and measuring cuvettes with light shield caps.

Accessories

29845	PRIMEIME Calibration Kit .02, 10, 1000 NTU
19856	Cuvettes with light shield caps, 3 pack

hf scientific
3170 Metro Parkway
Ft. Myers, FL 33916-7597
Phone: (239) 337-2116
Fax: (239) 332-7643
Email: hfinfo@watts.com
www.hfscientific.com

Represented by:

Standard Features

• **MicroTPW** - EPA ACCEPTED METHOD

• **MicroTPI** - CONFORMS TO ISO 7027

• **Rugged Self-Contained Carrying Case**
Contains everything needed, including battery pack, manual, and PRIMEIME calibration standards. Ensures durability and convenience regardless of where the sample needs to be taken.

• **Waterproof**
Water proof housing allows sample measuring and cleaning in any wet environment.

• **Auto Ranging 0 - 1100 NTU**
Instrument senses turbidity level of sample and automatically adjusts to the appropriate measurement range.

• **Simple Calibration Procedures**
Calibration initiated with the push of a button ensures accurate readings.

• **PrimeTime Standards Kit**
Each MicroTPW Turbidimeter is shipped with an HF PrimeTime Calibration kit manufactured using USEPA and ISO 7027 Accepted Primary Standard materials*.

• **Economical Cost**

• **Reusable Primary Standards**

• **Over 5000 Tests on a single set of 4 - AAA alkaline batteries.**

• **Lamp Life 7-10 years with normal use**

• **Built-In Self Diagnostics**

• **Manufactured in the USA.**



Simple Calibration Procedures



MicroTPW
with carrying case