





Enabling Australia's Field Technicians to build, troubleshoot and maintain better communications networks.



This reference material is provided by TMG Test Equipment, VIAVI's **only** Master Distributor for Contractors in Australia





Finance Available



Short to Medium Project-Based Rental Solutions



Dedicated Technical & After-Sales Support



In-house Diagnostics, Repair & NATA Calibration Laboratory





OLP-82/82P

SmartClass™ Fiber Power Meter and Microscope



Key Benefits

- Complete jobs faster, correctly, and on time—the first time Uniquely integrates fiber inspection and test for an efficient, easy-to-use solution that promotes best practices for handling fiber
- Analysis with pass/fail results on one handheld device
 Automatically and easily certifies fiber end-face condition and
 measures optical power making even new technicians fiber
 experts
- Easily generates certification reports

 Prove that work quality meets industry standards and customer specifications
- Use it anywhere
 A portable, organized, hands-free carrier for easy use inside homes, at demarcation points, or up on telephone poles and cell towers

Key Features

- Field-portable OPM with multiple calibrated wavelengths from 780 to 1625 nm
- Automated pass/fail analysis for fiber inspection and test
- Supports both industry-standard and user-definable acceptance criteria
- Available with integrated PCM
- Integrated connector certification reports
- Onboard storage for fiber inspection and test results
- Connects to a PC via mini-USB to export data and manage acceptance criteria using FiberChekPRO™ software
- Two USB ports to connect additional devices such as a P5000i microscope
- Automatic fiber-image centering
- Modern, smartphone-style user interface with touch screen
- Rugged, weather-proof design

The new OLP-82 from JDSU is the first handheld tool to combine pass/fail fiber inspection and optical power measurement (OPM) into one solution. As part of the new JDSU SmartClass Fiber Family, the OLP-82 helps service providers guarantee a lifetime of system performance from their network connectivity and gives contractors an essential tool for delivering best-in-class reliable networks to their customers.

The OLP-82 is ideal for technicians at any skill level with instant pass/fail acceptance results for both end-face quality and OPM in one button push. The OLP-82 can also save test results and generate certification reports to document work quality. Integrating these capabilities into one system helps the OLP-82 drive technician behavior toward implementing today's best practices in a seamless workflow that optimizes efficiency and reliability so they complete the job right—the *first* time.

The handheld OLP-82 can be used anywhere today's fiber technicians go, up poles or down holes. Technicians get ultimate flexibility and performance from this powerful, easy-to-use solution that can help any technician become an instant fiber expert.

Become an instant fiber expert with SmartClass Fiber

- ✓ Integration
- ✓ Automation
- ✓ Ease of use

Combines inspection and testing

Pass/fail certification

Intuitive smartphone-style user interface



Intuitive smartphone-style user interface

High-contrast, color touch screen with menu icons



Store inspection and measurement readings on the device


Store up to 10,000 measurement results on the device for export to PC .





Accurate measurement and simple operation

Make quick, easy dual-wavelength measurements at 850 and 1300 nm or 1310 and 1550 nm using saved reference levels.



$User-definable\ pass/fail\ acceptance\ criteria$

Whether using the IEC 61300-3-35 or customer-specific requirements, users can easily manage user-specified acceptance criteria with dedicated profiles for each requirement.

Comprehensive data management and report generation

Easily generate certification reports that prove your quality of work meets industry standards or customer specifications using FiberChekPRO PC software.

- Easily store measurement data at the press of a button
- Manage data and store results on the instrument
- Download measurement results to a PC via USB interface



Inspect and test fiber anywhere

Combines inspection and test in one handheld device

Use either the onboard patch-cord microscope (PCM) or connect a P5000i digital analysis microscope to inspect fiber end faces and eliminate poor-quality components from entering your network

Benefits of using P5000i and PCM together

- Optimizes technician performance with tools designed for workflow
- Improves network activation with a reliable, repeatable processes
- Safely stores test leads when not in use
- Quickly and easily inspects both female (bulkhead) and male (patch cord) fiber connectors without changing tips

Automatic image centering

Centers the fiber image on the screen

Ultimate portability and organization

The hands-free carrier stores all of the essential tools, such as the inspection microscope, visual fault locator, and cleaning materials, in an organized, portable system that you can take with you to every job.

Specifications

General

General technical (Typical at 25°C)				
Weight	1.2 lb			
	(1.4 lb for PCM version)			
Dimensions (H x W)	(D)			
0LP-82	20.83 x 11.18 x 6.35 cm			
	(8.2 x 4.4 x 2.5 in)			
OLP-82P	20.83 x 152.4 x 6.35			
	(8.2 x 60 x 2.5 in)			
Video display	3.5 in color LCD, 4:3 ratio			
Keypad	11+2 dome-buttons membrane panels			
	4 LED indicators			
Connector	USB 2.0			
	(2 x host, Type A; 1 x device, Micro-B)			
Power source	AC adaptor, battery			
	(Alkaline or rechargeable Li ion), USB port			
Run time				
Rechargeable Li ion = (minimum) 8 h				
Alkaline	5 hours			
Power mode	Active, Auto-off			
Auto-shutoff time	user programmable			
Charge time				
AC adaptor	8 hours			
USB port	16 hours			
Power source	USB port			
Certification	CE, IEC/EN61326			
Warranty	1 year			

OPM

General technical (Typical at 25°C)				
Display range				
Standard	-65 to +10 dBm			
High power	-50 to +23 dBm			
Max. input level permitted				
Standard	+10 dBm			
High power	+23 dBm			
Standard wavelength settings	850, 980, 1300,			
	1310, 1490, 1550, 1625 nm			
Intrinsic uncertainty ¹	±0.20 dB (±5%)			
Linearity ¹	±0.06 dB			
	(-50 to +5 dBm)			
Wavelength range	780 to 1650 nm			
Wavelength and modulation				
Result display	dBm, dB, MW			
Resolution	0.01 dB			

Video Display

General technical (Typical at 25°C)				
Live image	320 x 240 x 8 bit gray, 10 fps			
Light source	Blue LED, 100,000+ hour life			
Lighting technique	Coaxial			
Low-magnification field-of-view (FOV)				
Horizontal	740 µm			
Vertical	550 μm			
High-magnification field of view (FOV)				
Horizontal	370µm			
Vertical	275 μm			



Ordering Information

FIT-8201-PRO

FIT-82P01-PRO

FIT-82P03-PRO

FIT-82P01

FIT-82P03

Stand-Alone	Units		
Part Number	Description		
FBP-HD4i	HD4i Digital Handheld Video Display		
FBP-HD4iP	HD4iP Digital Handheld Video Display,		
	Dual-Mag Patch Cord Module		
2315/01	OLP-82 Digital Handheld Video		
	Display, Integrated Optical Power Meter		
2315/03	OLP-82 Digital Handheld Video Display,		
	Integrated High-Power Optical Power Meter		
2316/01	OLP-82P Digital Handheld Video Display,		
	Dual-Mag Patch Cord Module, Integrated OPN		
2316/03	OLP-82P Digital Handheld Video Display,		
	Dual-Mag Patch Cord Module, Integrated		
	High-Power OPM		
Kits			
FBP-SD4i	HD4i Basic Kit		
FBP-SD4i-PRO	HD4i Pro Kit		
FBP-SD4iP	HD4iP Basic Kit		
FBP-SD4iP-PRO	HD4iP Pro Kit		
FIT-8201	OLP-82 Basic Kit		

OLP-82 Pro Kit

OLP-82P Basic Kit

OLP-82P Pro Kit

OLP-82P High Power, Basic Kit

OLP-82P High Power, Pro Kit

Stand-Alone Units				
SmartClass Fiber Instrument				
Soft Bag for SmartClass Fiber and Accessories				
Power Supply for SmartClass Fiber (12 V)				
FiberChekPRO Software Installation Disk				
USB Cable USB-A to Micro-USB				
QuickStart Manual and Safety Instructions				
Dry Batteries (8x)				
Additional Items in Basic Kits				
P5000i Digital Inspection Microscope				
Inspection Tips and Adapters (Bulkhead: SC and LC,				
Patch Cord: 2.5 and 1.25 mm)				
1.25 mm OPM Adapter OLP-82/82P				
Additional Items in Pro Kits				
P5000i Digital Inspection Microscope				
Inspection Tips and Adapters (Bulkhead: SC and LC,				
Inspection Tips and Adapters (Bulkhead: SC and LC, Patch Cord: 2.5 and 1.25 mm)				
Patch Cord: 2.5 and 1.25 mm)				
Patch Cord: 2.5 and 1.25 mm) 1.25 mm OPM Adapter OLP-82/82P				
Patch Cord: 2.5 and 1.25 mm) 1.25 mm OPM Adapter OLP-82/82P Cleaning Materials for 2.5 and 1.25 mm (Bulkhead and				
Patch Cord: 2.5 and 1.25 mm) 1.25 mm OPM Adapter OLP-82/82P Cleaning Materials for 2.5 and 1.25 mm (Bulkhead and Patch Cord)				
Patch Cord: 2.5 and 1.25 mm) 1.25 mm OPM Adapter OLP-82/82P Cleaning Materials for 2.5 and 1.25 mm (Bulkhead and Patch Cord) Hands-Free Carrier for SmartClass Fiber				
Patch Cord: 2.5 and 1.25 mm) 1.25 mm OPM Adapter OLP-82/82P Cleaning Materials for 2.5 and 1.25 mm (Bulkhead and Patch Cord) Hands-Free Carrier for SmartClass Fiber Rechargeable Battery for SmartClass Fiber (Li ion)				

Included Items

Accessories	
FBPP-PS4	Power Supply for SmartClass Fiber (12V)
FITP-RBP2	Rechargeable Battery for SmartClass Fiber
	(Li ion)
FITP-UC4	UC4 Hands-Free Carrier for SmartClass Fiber
FITP-UC4P	UC4P Hands-Free Carrier for SmartClass
	Fiber with PCM
VPP-UPP12	Adapter U12 for OLP-82/82P
VPP-UPP25	Adapter U25 for OLP-82/82P
FBPP-SCASE2	SCASE2 Soft Shoulder Case for SmartClass
	Fiber Tools

Test & Measurement Regional Sales

NORTH AMERICA	LATIN AMERICA	ASIA PACIFIC	EMEA	www.jdsu.com/test
TOLL FREE: 1 855 ASK-JDSU	TEL: +1 954 688 5660	TEL: +852 2892 0990	TEL: +49 7121 86 2222	-
1 855 275-5378	FAX: +1 954 345 4668	FAX: +852 2892 0770	FAX: +49 7121 86 1222	