



ABN 43 064 478 842

231 Osborne Avenue Clayton South, VIC 3169  
PO Box 1548, Clayton South, VIC 3169  
t 03 9265 7400 f 03 9558 0875  
freecall 1800 680 680  
www.tmgtestequipment.com.au

## Test & Measurement

- > sales
- > rentals
- > calibration
- > repair
- > disposal

## Complimentary Reference Material

This PDF has been made available as a complimentary service for you to assist in evaluating this model for your testing requirements.

TMG offers a wide range of test equipment solutions, from renting short to long term, buying refurbished and purchasing new. Financing options, such as Financial Rental, and Leasing are also available on application.

TMG will assist if you are unsure whether this model will suit your requirements.

Call TMG if you need to organise repair and/or calibrate your unit.

If you click on the "Click-to-Call" logo below, you can call us for FREE!

TMG Corporate Website

TMG Products Website



Click-to-Call  
TMG Now



Product Lifecycle Management System

### Disclaimer:

All trademarks appearing within this PDF are trademarks of their respective owners.





## FEATURES

- TestWizard™ – True One-button Testing
- Volt-Ohm Meter
- Transmission Tests with xDSL, ISDN, and POTS Capability
- Load Coil Counter
- Longitudinal Balance
- Open (Capacitance) Meter
- Resistance Fault Locator
- Full Function TDR with Automatic Multiple Event Marking
- Flexible, Upgradeable Platform
- Complete On-Line Help and Tutorials
- Rugged Design – Survives 2 m drop
- Automatic Hazardous Voltage Safety Warning
- Extra Large, High-Contrast, Backlit Display

## APPLICATIONS:

If your job is to analyze and troubleshoot the access network for analog or digital services, the Tempo TelScout® TS200 is built for you. Designed specifically for telephone access network applications, including xDSL, ISDN, and POTS, the TelScout TS200 applies the newest technology to provide both ease-of-use and telephony performance that cannot be found in any other access network analyzer.

**TestWizard™ Analysis**

With the TelScout TS200, you'll spend less time operating the instrument, and more time analyzing and repairing faults. The TelScout TS200 can be configured to perform a variety of tests to meet your specific needs. The strength of the TelScout TS200 is its ability to perform logical test sequences that lead the operator toward potential troubleshooting solutions. With TestWizard™ analysis, this innovative solution is just a single button press away!

**TelScout TS200 – Designed for Your Needs**

With true multi-function test capability, the TelScout TS200 is designed for easy upgradeability to meet your future needs. You get all this flexibility and performance in one of the industry's most rugged access network packages. Come snow, rain, heat, and humidity, the TelScout TS200 keeps working, because you have to.



**TelScout®  
TS200  
Characteristics**

**xDSL/ISDN/POTS**

**AC Voltage –**

Range: 0 to 300 V.  
Resolution: 0.1 V.  
Accuracy: ±(1% + 0.5 V).

**DC Voltage –**

Range: 0 to ±400 V.  
Resolution: 0.1 V.  
Accuracy: ±(1% + 0.5 V).

**Loop Current –**

Range: 0 to 300 mA.  
Resolution: 0.1 mA.  
Accuracy: ±1% @ 60 mA.

**Resistance –**

Range: 0 to 1 k Ω  
Resolution: 0.1 Ω  
Accuracy: ±(0.9% + 1.0 Ω + 1 count).  
Range: 1 k Ω to 100 k Ω  
Resolution: 10 Ω  
Accuracy: ±0.9% + 1 count.  
Range: 100 k Ω to 1 M Ω  
Resolution: 100 Ω  
Accuracy: ±1% + 1 count.  
Range: 1 M Ω to 100 M Ω  
Resolution: 100 k Ω  
Accuracy: ±6% + 1 count.

**Load Coil Counter –** Range: 0 to 7 Load Coils.

**Ringers –**

Range: 0 to 5 REN.  
Resolution: 0.1 REN.  
Accuracy: ±0.5 REN (C4 type ringers).

**Ohms/Distance Calculator –**

Resistance Range: 0 to 9999 Ω  
Distance Range: 0 to 60 km (200 kft.).

**Loss –**

Frequency Range: 20 Hz to 200 kHz.  
Frequency Resolution: 1 Hz.  
Frequency Accuracy: ±2 Hz @ 0 dBm.  
Level Range: -40 to +10 dBm.  
Level Resolution: 0.1 dB.  
Level Accuracy:  
300 Hz to 4.5 kHz: ±0.5 dB.  
40 kHz: ±2.0 dB.  
196 kHz: ±4.0 dB.  
Z<sub>in</sub>: 600 Ω (Z<sub>ref</sub> = 135 Ω above 20 kHz).

**Noise –**

Range: 0 to 50 dBmC (dBm).  
Resolution: 0.1 dB.  
Accuracy: ±2.0 dB + Filter Accuracy.  
Z<sub>in</sub>: 600 Ω

**Power Influence –**

Range: 40 to 100 dBmC (dBm).  
Resolution: 0.1 dB.  
Accuracy: ±2.0 dB + Filter Accuracy.

**Slope –**

Frequency Range: 20 Hz to 200 kHz.  
Frequency Resolution: 1 Hz.  
Frequency Accuracy: ±2 Hz at 0 dBm.  
Level Range: -40 to +10 dBm.  
Level Resolution: 0.1 dB.  
Level Accuracy:  
300 Hz to 4.5 kHz: ±0.5 dB.  
40 kHz: ±2.0 dB.  
196 kHz: ±4.0 dB.

**Tracing Tone (Continuous or Intermittent) –**

Frequency: 577.5 Hz.  
Level: -40 to +10 dBm.  
Accuracy: ±1 Hz.

**Preset Tones –**

Frequency Range: 404 Hz, 577.5 Hz, 820 Hz, 1004 Hz, 1020 Hz, 2713 Hz, 2804 Hz, 5000 Hz, 28 kHz, 32 kHz, 40 kHz; plus 3-, 6-, and 10-step tone sequences.  
Frequency Resolution: 1 Hz.  
Frequency Accuracy: ± 2 Hz (20 Hz to 20 kHz).  
Level Range: -40 to +10 dBm.  
Level Resolution: 1 dB.  
Level Accuracy: ±0.5 dB above -25 dBm.

**User Defined Tones –**

Frequency Range: 20 Hz to 65 kHz.  
Frequency Resolution: 1 Hz.  
Frequency Accuracy: ±2 Hz (20 Hz to 20 kHz).  
Level Range: -40 to +10 dBm.  
Level Resolution: 1 dB.  
Level Accuracy: ±0.5 dB above -25 dBm.

**Longitudinal Balance –**

Range: 40 to 62 dB.  
Resolution: 0.1 dB.  
Accuracy: ±2 dB.

**Dialer –** DTMF or Pulse.

**Open Meter –**

Range: 0 to 300 m (1 kft.).  
Resolution: 0.5 m (1 ft.).  
Range: 300 m to 60 km (1 kft. to 200 kft.).  
Resolution: 3 m (10 ft.).  
Accuracy: ±1% @ 3 km (10 kft.).

**Capacitance –**

Range: 10 pF to 10 nF.  
Resolution: 10 pF.  
Range: 10 nF to 10 μF.  
Resolution: 10 nF.  
Accuracy: ±(1% + 50 pF + 1 count) up to 3.5 μF.

**Resistance Fault Locator –**

Fault Resistance Range: 0 to 40 M Ω  
Distance Range: 0 to 60 km (200 kft.).  
RTF Range: 0 to 400 Ω  
RTF Resolution: 0.01 Ω  
RTF Accuracy: ±(0.9% ±1.0 Ω + 1 count).  
RTF Range: 400 Ω to 4 k Ω  
RTF Resolution: 0.1 Ω  
RTF Accuracy: ± 0.9% + 1 count.  
RTF Range: 4 k Ω to 40 k Ω  
RTF Resolution: 1 Ω  
RTF Accuracy: ±0.9% + 1 count.

**TDR**

**Test Signal Output –** 1/2 sine, 1.55 to 31 V<sub>p-p</sub>.  
**Pulse Widths –** 2, 10, 75, 340, 3400 ns.

**Output Impedance –** 105 Ω typical.

**Maximum Range –** 15,000 m (50,000 ft.), depending on cable type and condition.

**Gain –** 0 to 72 dB.

**Input Protection –** ±400 VDC + peak AC at power line frequencies, maximum duration up to 30 sec.

**Waveform Storage –** Up to 20 waveforms with notes.

**Horizontal Design Accuracy –** 0.1% ± 300 ps ± V<sub>p</sub> uncertainty ± cursor resolution.

**Cursor Resolution –** 0.33% of selected range.

**Display Ranges –** 15 display ranges plus single-button zoom window. Ranges are user definable in manual mode.

**Display Modes –** Test, Splits (Crosstalk), Test/Reference, Test/Difference/Reference, Difference, Intermittent, Saved, Test/Saved, Test/Difference/Saved, Reference.

**General  
Characteristics**

**ENVIRONMENTAL**

**Temperature –**

Operating: -15°C to + 60°C.  
Non-operating: -30°C to +65°C.  
Performance Characteristics: 0°C to +45°C.

**Humidity –** 95% RH, non-condensing.

**Shock –** Survives drop of 2 m (6.6 ft.) to concrete in standard soft case.

**STANDARDS COMPLIANCE**

ISO9001.  
CE.  
UL 3111.1.  
CAN/CSA-C22.2 #1010.1.  
89/336/EEC.  
73/23/EEC.  
EN55011.

**POWER**

**Mains Operation –** Voltage Ranges: 100 V, 110 V, 230 V, 240 V with appropriate AC to DC adapter.

**Battery Operation –**

Operating Time: 8 hours at 50% duty cycle with internal NiMH battery.  
Battery Saver: Selectable from 1 to 30 minutes or disabled.  
Removable Battery Holder: Supports "AA" (LR6) alkaline batteries.

**PHYSICAL**

| Dimensions | cm  | in. |
|------------|-----|-----|
| Height     | 22  | 8.5 |
| Width      | 25  | 10  |
| Depth      | 7   | 2.7 |
| Weight     | kg  | lb. |
| Net        | 2.4 | 5.4 |

**INTERFACES**

**Display –** High resolution VGA, 640 x 480 pixels, 6.2-inch high contrast. Operator switchable backlight.

**Serial Port –** 9-pin D-type serial connector.  
**Speaker –** Used only on TS200-03

**WARRANTY**

One year parts and labor.

**Ordering  
Information**

**TelScout® TS200 Access Network Analyzer**

Includes: Test Leads (012155200), Soft Carrying Case (016169000), U.S. AC Adapter/Charger (119603100), U.S. Line Cord (161022800), Vehicle DC Adapter (012155300), Internal NiMH Battery (146012600), Alkaline Battery Adapter (352107100), User Manual (071006900).

**TS200 Functionality Options**

(must choose one)

**Option 01 –** TDR capability.

**Option 03 –** TDR and xDSL/ISDN/POTS capability (includes Waist Strap, 346029200).

**International Power Cord Options**

**Option 1C –** Universal Euro 220 V, 50 Hz (161006609).

**Option 2C –** UK 240 V, 50 Hz (161006610).

**Option 3C –** Australian 240 V, 50 Hz (161006611).

**Option 6C –** Japan 110 V, 50 Hz (161028800).

**Calibration and Test Data Options**

**Option C3 –** Three Years Calibration Service

**Option C5 –** Five Years Calibration Service

**Option D1 –** Test Data Report

**Option D3 –** Three Years Test Data (requires Option C3)

**Option D5 –** Five Years Calibration Service (requires Option C5)

**TS200 Recommended Accessories**

**Hard Travel Case –** 016121000.

**Strand Hook –** RFMSHA.

**D-Ring Hook –** 354074500.

**Waist Strap –** 346020200.

**PC Software for TDR –** MCTAP.  
**Serial Printer Cable, DB9-to-DB9 –** 012137900.

**Coaxial Cable Adapter, 75 Ω Banana-to-Type F –** 174352500.

**Extra Battery Pack –** 146012600.

**International Language Options**

**Standard –** English.

**Option L1 –** French.

**Option L3 –** German.

**Option L4 –** Spanish.

**Option L6 –** Portuguese.

**Option LA –** Australian.

**Option LD –** Dutch.