

ABN 43 064 478 842

231 osborne avenue clayton south, vic 3169 PO box 1548, clayton south, vic 3169 t 03 9265 7400 f 03 9558 0875 freecall 1800 680 680

www.tmgtestequipment.com.au

Test & Measurement

- sales
- rentals
- calibration
- repair
- disposal

Complimentary Reference Material

This PDF has been made available as a complimentary service for you to assist in evaluating this model for your testing requirements.

TMG offers a wide range of test equipment solutions, from renting short to long term, buying refurbished and purchasing new. Financing options, such as Financial Rental, and Leasing are also available on application.

TMG will assist if you are unsure whether this model will suit your requirements.

Call TMG if you need to organise repair and/or calibrate your unit.

If you click on the "Click-to-Call" logo below, you can all us for FREE!

TMG Corporate Website TMG Products Website Leuel 4 Disposal Disposal Click-to-Call TMG Now ○ Leuel 5 Review & Leuel 3 Repair Renew Review & Renew Repair Calibration Calibration Recycled Acquisition Leuel 1 Acquisition **Purchase** Lease Solution Centre Rent

Product Lifecycle Management System

Disclaimer:

All trademarks appearing within this PDF are trademarks of their respective owners.









Automatic RELAY TESTER model: RTS-373



Main features

- Tri-phase current, quad-phase voltage output, classic windows operating system, friendly interface, easy and fast operation
- 8.4" LCD display screen provides visual status, next step information
- Ultra thin 101 standard keyboard and optical mouse amd external USB interface
- Generates accurate signal of pure sine wave
- Directly outputs: AC voltage, AC current, DC voltage, DC current, variable amplitude, phase, frequency, 2-20 times harmonic waveform.
- Carry out complex verification works. Real time test data storage, display the vector and print the reports etc.
- Well designed cabinet, small size, fault diagnosis and automatic locking function



Automatic RELAY TESTER model: RTS-373

Introduction: Model 'RTS-373' is an ideal, newly developed multifunction relay tester adopting monolithic computer technology. It is composed of auto synchronized digital millisecond timer, logic controlling unit, multifunction digital display, high precision digit collection and processing unit, current-voltage output unit, overload and over range protection unit. Test process is automatic for improved efficiency.

Technical Specifications

Supply voltage	: 180 to 250V AC 50/60 Hz, single phase
AC Current source	: AC amplitude: 0-40A/phase; 3-phase parallel: 0-120A
	Accuracy: =0.5%
	Response time: =200µS
DC Current source	: DC amplitude: -10A to +10A /phase
	Accuracy: =0.5%
AC Voltage source	: AC amplitude: 0-120V/phase
_	Accuracy: =0.5%
	Response time: =120µS
DC Voltage source	: DC amplitude: -150V to +150V /phase
	Accuracy: =0.5%
Phase	: 0-360°
	Accuracy: 0.5°
Frequency	: 1-1000 Hz
	Accuracy: for $50 \text{ Hz} = 0.005 \text{Hz}$.
	An arbitrary superposition of harmonic amplitude overlapped by 2-
	20 times.
Input	: 8-Channel, Automatic identification of the polarity of active contacts.
	Accuracy: =1mS.
Output	: 4 pairs 250V DC, 0.5A/250V AC, 0.5A
	GPS: =50µS
USB Port	: USB port for connect9ing to PC.
GPS triggering	: Synchronization error: =50µS
Dimensions	: 42 x 36 x 19 cm approximately
Weight	: 18 kg approximately

Specifications subject to change due to constant upgradation

Catalog # RTS-373

[international source of power utility T & M equipments]

212-A H.S.Industrial Estate, 85/86 MV Road, Mumbai 400 059 www.udeyraj.com e-mail:udeyraj@vsnl.com Ph: 022 66916181 Fax: 022 66942787