

ABN 43 064 478 842

231 osborne avenue clayton south, vic 3169 PO box 1548, clayton south, vic 3169 t 03 9265 7400 f 03 9558 0875 freecall 1800 680 680

www.tmgtestequipment.com.au

Test & Measurement

- sales
- rentals
- calibration
- repair
- disposal

Complimentary Reference Material

This PDF has been made available as a complimentary service for you to assist in evaluating this model for your testing requirements.

TMG offers a wide range of test equipment solutions, from renting short to long term, buying refurbished and purchasing new. Financing options, such as Financial Rental, and Leasing are also available on application.

TMG will assist if you are unsure whether this model will suit your requirements.

Call TMG if you need to organise repair and/or calibrate your unit.

If you click on the "Click-to-Call" logo below, you can all us for FREE!

TMG Corporate Website TMG Products Website Leuel 4 Disposal Disposal Click-to-Call TMG Now ○ Leuel 5 Review & Leuel 3 Repair Renew Review & Renew Repair Calibration Calibration Recycled Acquisition Leuel 1 Acquisition **Purchase** Lease Solution Centre Rent

Product Lifecycle Management System

Disclaimer:

All trademarks appearing within this PDF are trademarks of their respective owners.









Automatic RELAY TESTER model: RTS-963



Introduction: Model 'RTS-963' is an ideal, newly developed multifunction relay tester adopting monolithic computer technology. It is composed of auto synchronized digital millisecond timer, logic controlling unit, multifunction digital display, high precision digit collection and processing unit, current-voltage output unit, overload and over range protection unit. Test process is automatic for improved efficiency. The tester has a built in printer for printing the results.

Features:

Micro-computer controlled: Self test function and error reporting
Audio + Visual warning and automatic cut-off for overload and over range
Highly intelligent: One key tests and prints complete parameters of universal relay
LED display screen
Tests AC 'live-line' contacts



Automatic RELAY TESTER model: RTS-963

Application: For testing various AC/DC current, volt, intermediate, self perpetuating, signal, protection for switching in voltage [current] value for various relays. The switching in time and breaking time for various contacts [normally open, normally closed, changeover, time delay] are tested three times automatically, readings are stored and automatically the mean value of three readings is calculated and printed. Re-closing relays can also be tested. 'RTS-963' is equipped with frequency and phase testing function to test frequency of current, voltage [display time for a cycle] and phase difference between signals. 'RTS-963' has two independent channels, insulated from the other output and can easily test live-line contact. 'RTS-963' adopts accurate time counting reference [10 microseconds] and can serve as a precision independent millisecond counter to replace traditional seconds counter.

Specifications

Input : $240 \pm 5\%$ Volts AC, 50 Hz, Single phase

AC voltage output : 0-250 volts maximum capacity of 600VA

Over range protection: 260 volts

AC current output : 0-50 amps open circuit voltage of 10 volts

0-100 amps open circuit voltage of 5 volts

Over load protection: 120 amps

AC voltage output : 0-250 volts continuous maximum current 2 amps

Over range protection: 260 volts

Over load protection: 2.1 ± 5% [buckle wave co-efficient is S=0.1.

DC current output : 0-200mA; open circuit voltage 48V; over-load protection: 230mA

0-5Amp; ; open circuit voltage 24V; over-load protection: 5.2A

Fixed DC-V output : Independent output: 110V or 220V at 2.5A

Millisecond meter : 5 digit, auto synchronized millisecond counter. Maximum range of

100 hours. Resolution: 0.01 millisecond

Accuracy: 0.01% ± 1 digit

Output Accuracy : ±1%

Dimensions : 46 x 32 x 31 cm [approximately]

Weight : 20 kg [approximately]