

ABN 43 064 478 842

231 osborne avenue clayton south, vic 3169 PO box 1548, clayton south, vic 3169 t 03 9265 7400 f 03 9558 0875 freecall 1800 680 680

www.tmgtestequipment.com.au

# Test & Measurement

- sales
- rentals
- calibration
- repair
- disposal

### **Complimentary Reference Material**

This PDF has been made available as a complimentary service for you to assist in evaluating this model for your testing requirements.

TMG offers a wide range of test equipment solutions, from renting short to long term, buying refurbished and purchasing new. Financing options, such as Financial Rental, and Leasing are also available on application.

TMG will assist if you are unsure whether this model will suit your requirements.

Call TMG if you need to organise repair and/or calibrate your unit.

If you click on the "Click-to-Call" logo below, you can all us for FREE!

#### **TMG Corporate Website TMG Products Website** Leuel 4 Disposal Disposal Click-to-Call TMG Now ○ Leuel 5 Review & Leuel 3 Repair Renew Review & Renew Repair Calibration Calibration Recycled Acquisition Leuel 1 Acquisition **Purchase** Lease Solution Centre Rent

### Product Lifecycle Management System

#### **Disclaimer:**

All trademarks appearing within this PDF are trademarks of their respective owners.









# TIME INTERVAL METER TIM-1



### **Applications:**

Measuring time interval. 'NO / NC' contacts. Stop watch.

#### Introduction:

The UDEY 'TIM-1' is a high precision, new generation test set using crystal base for measurements.

#### **Features:**

Digital display in 4 digits.

Multi-range: to 9999 seconds in five ranges Portable light weight.



# TIME INTERVAL METER TIM-1

## **SPECIFICATIONS:**

Power supply	: 220V±10%, AC 50 Hz
Measuring Rang	: .9999 / 9.999 / 99.99 / 9999 seconds
Measuring accuracy	: ±0.05 ±1 count
Display	: LED 12.5 mm; 4 digit with decimal
Signal voltage	: AC/DC: 24 to 240V
Impedance	: 15 k
Contacts	: OPEN: 100K or more CLOSED: 100 ohm or less
Protection	: up to 250V AC/DC
Operation	: Time interval measurement; stop watch.
Usage environment	: Less than 45° C. Less than 85% R.H.
Enclosure	: ABS body with tilting handle.
Dimensions	: 21.5(W)x23(D)x9(H) cm approx.
Weight	: 2.0 kg approx.
Accessories	: Power supply cord 3 core. Flexible testing cable set with alligator clamps. Operating Manual.

Specs subject to change due to constant up gradation Catalog # TIM-1