

ABN 43 064 478 842

231 osborne avenue clayton south, vic 3169 PO box 1548, clayton south, vic 3169 t 03 9265 7400 f 03 9558 0875 freecall 1800 680 680

www.tmgtestequipment.com.au

# Test & Measurement

- sales
- rentals
- calibration
- repair
- disposal

## **Complimentary Reference Material**

This PDF has been made available as a complimentary service for you to assist in evaluating this model for your testing requirements.

TMG offers a wide range of test equipment solutions, from renting short to long term, buying refurbished and purchasing new. Financing options, such as Financial Rental, and Leasing are also available on application.

TMG will assist if you are unsure whether this model will suit your requirements.

Call TMG if you need to organise repair and/or calibrate your unit.

If you click on the "Click-to-Call" logo below, you can all us for FREE!

### **TMG Corporate Website TMG Products Website** Leuel 4 Disposal Disposal Click-to-Call TMG Now ○ Leuel 5 Review & Leuel 3 Repair Renew Review & Renew Repair Calibration Calibration Recycled Acquisition Leuel 1 Acquisition **Purchase** Lease Solution Centre Rent

## Product Lifecycle Management System

#### **Disclaimer:**

All trademarks appearing within this PDF are trademarks of their respective owners.







DC - 10.0 GHz 25 WATTS



## Features

Type N, SMA or TNC stainless steel M/F connectors per MIL-STD-348A, interface dimensions mate nondestructively with MIL-PRF-39012.

## Specifications


Nominal Impedance: 50 ohms

Frequency Range: DC – 10.0 GHz

**Power Rating:** 25 watts average. Maximum rated average power to 25°C ambient temperature, derated linearly to 2.5 watts at 125°C. 1 kilowatt peak (5 µsec pulse width; 1.5% duty cycle).

Temperature Range: -55°C to +125°C

**Calibration:** VSWR performed across frequency range. Calibration test data available at additional cost.



**Construction:** Black aluminum alloy body with passivated stainless steel connectors. Gold plated beryllium copper female contacts.

#### **Maximum VSWR:**

Frequency (GHz)	VSWR
DC - 4.0	1.10
4.0 – 10.0	1.15

**Weight:** .17 kg/ 6 oz

**Physical Dimensions:** 

Length:

Connector Type	DIM "A"
Type N Female -3	60.99 (2.4)
Type N Male -4	68.57 (2.7)
SMA Female -1	58.43 (2.3)
SMA Male -2	60.99 (2.4)

Note: Dimensions are given in mm (inches) and are maximum, unless otherwise specified



WEB: http://www.WeinschelAssociates.com EMAIL: sales@WeinschelAssociates.com