

ABN 43 064 478 842

231 osborne avenue clayton south, vic 3169 PO box 1548, clayton south, vic 3169 t 03 9265 7400 f 03 9558 0875 freecall 1800 680 680

www.tmgtestequipment.com.au

Test & Measurement

- sales
- rentals
- calibration
- repair
- disposal

Complimentary Reference Material

This PDF has been made available as a complimentary service for you to assist in evaluating this model for your testing requirements.

TMG offers a wide range of test equipment solutions, from renting short to long term, buying refurbished and purchasing new. Financing options, such as Financial Rental, and Leasing are also available on application.

TMG will assist if you are unsure whether this model will suit your requirements.

Call TMG if you need to organise repair and/or calibrate your unit.

If you click on the "Click-to-Call" logo below, you can all us for FREE!

TMG Corporate Website TMG Products Website Leuel 4 Disposal Disposal Click-to-Call TMG Now ○ Leuel 5 Review & Leuel 3 Repair Renew Review & Renew Repair Calibration Calibration Recycled Acquisition Leuel 1 Acquisition **Purchase** Lease Solution Centre Rent

Product Lifecycle Management System

Disclaimer:

All trademarks appearing within this PDF are trademarks of their respective owners.







Broadband Resistive Power Divider MODEL WA1574

DC - 26.5 GHz 1 WATT



AMPLITUDE & PHASE TRACKING (MAX.)		
Frequency (GHz)	Tracking	
	Amplitude	Phase
DC - 26.5	< 1.0	< 2 °

Features

Lightweight Miniature package: High power capability. These resistive power dividers are intended for RF and wireless applications in which the signal must be divided or combined.

Expectations

NOMINAL IMPEDANCE: 50Ω

FREQUENCY RANGE: DC - 26.5 GHz

INSERTION LOSS: 6 dB nominal, 8.5 dB maximum

(between input and either output).

MAXIMUM INPUT POWER: 1.0 watt CW, 1kw peak (5 µsec pulse width, 0.05 % duty cycle, input connector only).

TEMPERATURE RANGE: -55°C to +125 °C

TEMPERATURE COEFFICIENT: < 0.004 dB/dB/°C

POWER COEFFICIENT: < 0.005 dB/dB/watt

CONTRUCTION: Nickel plated brass body;

stainless steel connectors.

MAXIMUM VSWR		
Frequency (GHz)	VSWR	
DC - 26.5	1.70	

CONNECTORS: Male 3.5mm port 1, (2) Female 3.5mm ports 2 and 3; all ports-mate nondestructively with other SMA, 2.92mm and 3.5mm connectors. Optional female 3.5mm connectors are available on all ports.

WEIGHT: 25 g (0.9 oz) maximum

PHYSICAL DIMENSIONS:

Body Width: 10.2 (0.40)

Body Height: 15.2 (0.60) Square

NOTE: All dimensions are given in mm (inches) and are maximum, unless otherwise specified.



WEB: http://www.WeinschelAssociates.com EMAIL: sales@WeinschelAssociates.com