
## **RADIODETECTION**<sup>®</sup>

# Submersible Double Depth Antenna



#### **Features overview**

- Alternative antenna for Precision series locator which doubles effective depth range.
- Submersible to 100m/328ft depth.
- Has neutral buoyancy with brass weight on lower end for stability.
- Locator Depth button pressed as normal for depth measurement.
- Liquid crystal display locator depth calculation performed automatically (moving coil meter locator requires operator calculation).
- Supplied with 10m/33ft (or Customer specified length) of submersible cable and jumper cable which connects to locator accessory socket.
- Identification plate displays:
  - Serial number of antenna.
  - Serial number of Precision series locator used for test.
  - Matched locator calibration frequency.
- Can be suspended from non-metallic boom and lowered to sea/river bed.
- No batteries required.

### **Technical Specification**

Description:	Submersible double depth antenna.
Part No:	<b>10/RX-SUBANTENNA-XX</b> Replace <b>XX</b> with 512, 640 or 8k for required frequency of operation.
Specification:	Antenna.
Physical:	
Construction:	Polypropylene.
Dimensions:	106cm x 25cm x 11cm (41.7" x 9.8" x 4.3").
Weight:	9kg/20lb (10m/33ft cable fitted).
Shipping Weight:	10kg/22lb (10m/33ft cable fitted).
Shipping Box: Size:	135cm x 31cm x 21cm (53.1" x 12.2" x 8.3").
Accuracy:	
Locate Accuracy:	±5% of depth.
Depth Accuracy:	Line 6m/20ft ±5%, Sonde 15m/50ft ±5%.
Current Accuracy:	±5% of actual current.
Frequency:	512Hz (typical), 640Hz (typical) or 8kHz (typical).
Search Antennas:	2 x dual wound symmetrical antennas for for Peak operation.
Operating Temperature Range:	-20°C to +50°C (-4°F to +122°F).
Power Supply:	Supplied by locator via accessory socket.
Interconnecting cable:	10m/33ft or Customer specified length of submersible cable type. Typical weight: 130kg/km.
Sealing:	100m/328ft depth IP68.
Miscellaneous:	
Quality Control:	ISO 9001:2015.
Warranty:	12 months.
Compatibility:	Any Precision series locator fitted with accessory socket.



#### www.contractoressentials.com.au

#### www.tmg.com.au

## Head Office TMG Test Equipment 231 Osboune Avenue, Clayton South Victoria 3169 1800-680-680

Copyright © 2019 Radiodetection Ltd. All rights reserved. Radiodetection is a subsidiary of SPX Corporation. Radiodetection is a registered trademark of Radiodetection in the United States and/or other countries. Due to a policy of continued development, we reserve the right to alter or amend any published specification without notice. This document may not be copied, reproduced, transmitted, modified or used, in whole or in part, without the prior written consent of Radiodetection Ltd.