

# ATC200-LITE-USB

---



## Portable Controller

- Carried from site to site for RET antenna setup and optimization
- Supports up to 32 RET actuators operating in AISG 1.1 or 2.0 modes
- LED display indicates the presence of input power, output power, and data communication
- Equipped with USB and serial connectors
- Power supply efficiency is Energy Star® Level IV rated

## Product Classification

**Product Type** RET controller

## General Specifications

**AISG Output Connector** 8-pin DIN Female

**AISG Output Connector Quantity** 1

**Auxiliary Interface** USB

**Color** Gray | Yellow

## Dimensions

**Height** 50.8 mm | 2 in

**Width** 127 mm | 5 in

**Depth** 76.2 mm | 3 in

## Electrical Specifications

**Input Voltage** 110/240 Vac

**Output Current at Voltage, continuous** 3.0 A @ 24 V

**Output Current at Voltage, maximum** 3.0 A @ 24 V

**Output Voltage, typical** 24 V

**Electrical Safety Standard** CB | CE | IEC 60950-1

**Interface Protocol Signal** Data | dc

**Power Supply** dc Jack

**Protocol** AISG 1.1 | AISG 2.0

## Material Specifications

**Material Type** Aluminum

# ATC200-LITE-USB

---

## Environmental Specifications

**Operating Temperature** -40 °C to +55 °C (-40 °F to +131 °F)

**Relative Humidity** Up to 95%, non-condensing

## Packaging and Weights

**Included** Control unit | Power supply | Site configuration worksheet | US adapter | USB cable

**Weight, net** 0.4 kg | 0.882 lb

## Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on <a href="http://www.commscope.com/ProductCompliance">www.commscope.com/ProductCompliance</a>
ROHS	Compliant

